

11-22-00

PTO/SB/05 (08-00)

Please type a plus sign (+) inside this box → ☐

Approved for use through 10/31/2002. OMB 0651-0032

U.S. Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

11/21/00

11/21/00

# UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. 36767YBB

First Inventor Arvin D. Danielson

Title Laser Scanner Module Having Integral Interface with Hand-Held Data Capture Terminal, Proximity and Label Sensing, and Enhanced Sensitivity and power efficiency

Express Mail Label No. EK 941 170 905 US

## APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. ☐ Fee Transmittal Form (e.g., PTO/SB/17)  
(Submit an original and a duplicate for fee processing)
2. ☐ Applicant claims small entity status.  
See 37 CFR 1.27.
3. ☒ Specification [Total Pages 89]  
(preferred arrangement set forth below)
  - Descriptive title of the invention
  - Cross Reference to Related Applications
  - Statement Regarding Fed sponsored R & D
  - Reference to sequence listing, a table, or a computer program listing appendix
  - Background of the Invention
  - Brief Summary of the Invention
  - Brief Description of the Drawings (if filed)
  - Detailed Description
  - Claim(s)
  - Abstract of the Disclosure
4. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 24]
5. Oath or Declaration [Total Pages 8]
  - a. ☐ Newly executed (original or copy)
  - b. ☒ Copy from a prior application (37 CFR 1.63 (d))  
(for continuation/divisional with Box 17 completed)
  - i. ☐ DELETION OF INVENTOR(S)  
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
6. ☐ Application Data Sheet. See 37 CFR 1.76

## ADDRESS TO:

Assistant Commissioner for Patents  
Box Patent Application  
Washington, DC 20231

7. ☐ CD-ROM or CD-R in duplicate, large table or Computer Program (Appendix)
8. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
  - a. ☐ Computer Readable Form (CRF)
  - b. Specification Sequence Listing on:
    - i. ☐ CD-ROM or CD-R (2 copies); or
    - ii. ☐ paper
  - c. ☐ Statements verifying identity of above copies

## ACCOMPANYING APPLICATION PARTS

9. ☐ Assignment Papers (cover sheet & document(s))
10. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) ☐ Power of Attorney
11. ☐ English Translation Document (if applicable)
12. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
13. ☐ Preliminary Amendment
14. ☒ Return Receipt Postcard (MPEP 503)  
(Should be specifically itemized)
15. ☐ Certified Copy of Priority Document(s)  
(if foreign priority is claimed)
16. ☒ Other: Change of Correspondence

17. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment, or in an Application Data Sheet under 37 CFR 1.76:

☒ Continuation ☐ Divisional ☐ Continuation-in-part (CIP)

of prior application No. 09, 189,778

Prior application information

Examiner

Mr. Harold Pitts

Group / Art Unit 2876

For CONTINUATION OR DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 5b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

## 18. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label

(Insert Customer No. or Attach bar code label here)

or ☒ Correspondence address below

Name John H. Sherman, Legal Department

Address Intermec Technologies Corporation  
550 2nd Street, S.E.

City Cedar Rapids State Iowa Zip Code 52401

Country USA Telephone 319-369-3661 Fax 319-369-3630

Name (Print/Type) John H. Sherman Registration No. (Attorney/Agent) 16,909

Signature John H. Sherman Date Nov. 21, 2000

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231

EXPRESS MAIL LABEL  
EK 941 170 905 US

PATENT APPLICATION  
Attorney Docket No. 36767YBB

IN THE UNITED STATES  
PATENT AND TRADEMARK OFFICE

**TITLE: "LASER SCANNER MODULE HAVING INTEGRAL  
INTERFACE WITH HAND-HELD DATA CAPTURE  
TERMINAL, PROXIMITY AND LABEL SENSING, AND  
ENHANCED SENSITIVITY AND POWER EFFICIENCY"**

**CROSS REFERENCES TO RELATED APPLICATIONS**

**a. Claiming Benefit Under 35 U.S.C. 120**

The present application is a continuation of copending Serial No. 08/215,115, DN36767YXA, filed March 17, 1994, which is a continuation-in-part of Serial No. 07/987,574, DN36767YXX, filed December 8, 1992, now U.S. Patent 5,313,053, issued May 17, 1994, which is a continuation application of Serial No. 07/674,756, DN36767YX, filed March 25, 1991, now abandoned, which is a continuation-in-part of PCT application PCT/US90/03282, DN36767X, filed June 7, 1990, which entered the U.S. national stage as Serial No. 07/777,393 with a filing date of December 6, 1991 and an effective date of January 7, 1992, currently pending, which is a continuation-in-part of both Serial No. 07/364,902, DN36767, filed June 8, 1989, now abandoned, and Serial No. 07/364,594 DN36808X, filed June 7, 1989, now abandoned.

Serial number 08/215,115 is also a continuation-in-part of application Serial No. 07/965,983, DN35726YA, filed October 23, 1992, now abandoned,

which is a continuation of Serial No. 07/719,731, DN35726Y, filed June 24, 1991, now abandoned, which is a continuation-in-part of Serial No. 07/441,007, DN35726X, filed November 21, 1989, now abandoned, which is a continuation-in-part of Serial No. 06/905,779, DN35726, filed September 10, 1986, now U.S. Patent 4,882,476, issued November 21, 1989. The disclosure of these applications are incorporated herein by reference in their entirety, including appendices and drawings.

Serial number 08/215,115 is also a continuation-in-part of application Serial No. 07/960,520, DN36767YZE, filed October 13, 1992, now abandoned, which is a continuation-in-part of application Serial No. 07/912,917, DN36767YZD, filed July 13, 1992, now abandoned, which is a continuation-in-part of Serial No. 07/881,096, DN36767YZC, filed May 11, 1992, now abandoned, which is a continuation-in-part of Serial No. 07/820,070, DN36767YZB, filed January 10, 1992, now abandoned, which is a continuation-in-part of Serial No. 07/786,802, DN36767YZA, filed November 5, 1991, now abandoned, which is a continuation-in-part of Serial No. 07/777,691, DN36767YZ, filed October 10, 1991, now abandoned, which is a continuation-in-part of Serial No. 07/735,610, DN36767YY, filed July 23, 1991, now abandoned, which is a continuation-in-part of 07/719,731, DN35726Y, filed June 24, 1991, now abandoned, which is a continuation-in-part of Serial No. 07/674,756, DN36767YX, filed March 25, 1991, now abandoned, which is a continuation-in-part of Serial No. 07/660,615, DN36767XZ, filed February 25, 1991, now U.S.

Patent 5,218,187, issued June 8, 1993, which is a continuation-in-part of Serial  
2 No. 07/633,500, DN6767XY, filed December 26, 1990, now U.S. Patent  
5,202,817, issued April 13, 1993, which is a continuation-in-part of Serial No.  
4 07/561,994, DN6649YX, filed July 31, 1990, now abandoned, which is a  
continuation-in-part of Serial No. 07/558,895, DN6649XZ, filed July 25, 1990,  
6 now abandoned, which is a continuation-in-part of Serial No. 07/426,135,  
DN6956, filed October 24, 1989, now U.S. Patent 5,218,188 issued June 8,  
8 1993, which is a continuation-in-part of Serial No. 07/347,849, DN6504XX, filed  
May 3, 1989, now abandoned, which is a continuation-in-part of Serial No.  
10 07/347,602, DN6649XX, filed May 3, 1989, now abandoned, which is a  
continuation-in-part of Serial No. 07/345,200, DN6649X, filed April 28, 1989,  
12 now abandoned, which is a continuation-in-part of Serial No. 07/305,302,  
DN6649, filed January 31, 1989, now abandoned.

14 Finally, the present application, DN6767YB, is a continuation-in-part of  
Serial No. 08/040,313, DN 5769Z, filed March 29, 1993, (pending) which is a  
16 continuation-in-part of Serial No. 07/451,322, DN5769Y, filed December 15,  
1989, now U.S. Patent 5,227,614, issued July 13, 1993, which is a continuation-  
18 in-part application of Serial No. 07/143,921, DN5769X, filed January 14, 1988,  
now abandoned, which is a continuation-in-part application of Serial No.  
20 06/897,547, DN5769, filed August 15, 1986, now abandoned, and the said  
application Serial No. 08/040,313 is further a continuation-in-part of Serial No.  
22 07/947,036, DN35740XYA, filed September 16, 1992, now U.S. Patent



5,308,966, issued May 3, 1994, which is a continuation of Serial No. 07/875,791,  
 DN35740XY, filed April 27, 1992, now abandoned, which is a continuation-in-  
 part of Serial No. 07/422,052, DN35740X, filed October 16, 1989, now  
 abandoned, which is a division of Serial No. 06/894,689, DN5740, filed August  
 8, 1986, now U.S. Patent 4,877,949, issued October 31, 1989.

**b. Incorporation by Reference**

The following related commonly owned patent applications are  
 incorporated herein by reference in their entirety, including appendices and  
 drawings:

<u>Inventor(s)</u>	<u>Serial No.</u>	<u>Filing Date</u>	<u>Patent No.</u>	<u>Issue Date</u>
Miller, et al.	07/136,097	12/21/87		
Danielson, et al.	07/143,921	01/14/88		
Koenck	07/238,701	08/31/88	5,019,699	05/28/91
Main, et al	07/321,932	03/09/89		
(for published version of 07/321,932, see continuation disclosure, identified by:				
Main, et al.	07/966,907	10/26/92	<u>5,216,233</u>	06/01/93)
Hanson, et al.	07/346,771	05/02/89		
Hanson, et al.	07/347,298	05/02/89		
Danielson, et al.	07/364,902	06/08/89		
(for application including the 07/364,902 disclosure, see:				
Danielson, et al.	07/777,393	01/07/92	issue fee paid)	
Chadima, et al.	07/339,953	04/18/89	4,894,523	01/16/90
Miller, et al.	07/347,602	05/03/89		
(for published version of 07/347,602, see continuation disclosure, identified by:				
Miller, et al.	08/046,048	04/12/93	5,331,580	07/19/94)
Danielson, et al.	07/422,052	10/16/89		
Koenck, et al.	07/467,096	01/18/90	5,052,020	09/24/91
Danielson, et al.	07/626,711	12/12/90		
Koenck, et al.	07/660,615	02/25/91	5,218,187	06/08/93
Koenck, et al.	07/987,574	12/08/92	5,313,053	05/17/94
Koenck, et al.	08/215,115	03/17/94		

Further, the following related commonly owned international patent  
 applications are incorporated herein by reference in their entirety:

	<u>International Application Number</u>	<u>International Filing Date</u>	<u>International Publication Number</u>	<u>International Publication Date</u>
<u>Inventor(s)</u>				
Koenck, et al.	US90/03282	06/07/90	WO90/16033	12/27/90
Koenck, et al.	US91/00435	01/18/91	WO91/11065	07/25/91

The entire disclosures of the foregoing publications are incorporated herein by reference.

#### BACKGROUND OF THE INVENTION

This invention relates to pocket size computer processor system means, and particularly to a plural module computer processor system capable of incorporating various data entry peripheral devices and of coupling with various data storage and data transmission devices while yet being suitable to be carried on the person of an individual user throughout a working day.

A long-standing problem in the hand-held computer field has been to provide a compact and efficient system for data capture while yet achieving low production cost. It is conceived that a breakthrough can be realized by an optimum plural module system configuration.

In another aspect, the invention relates to novel terminal means for association with information cards and is particularly concerned with such terminal means for use by an individual user in communication with another computer system. There are many circumstances for example where an individual may desire to carry out transactions with a central computer processing station. In one example, a racing establishment such as a horse racing organization may desire to enable individual members having accounts

with the organization to place bets from various locations such as home or office.

2 In such a circumstance, it would be highly advantageous if the individual could  
communicate directly with a central computer system placing with the system all  
4 the information concerning a bet, and receive from the computer system  
essentially instantaneous information as to whether such a bet has been  
6 accepted. Another example relates to food service functions where orders may  
be transmitted to a central order processing center, and where credit or debit  
8 card purchases may be approved and/or related data stored at the central  
processor. Still another example is in the field of direct store delivery of  
10 merchandise. A pocket size terminal may contain the necessary information  
concerning the items being delivered and may be coupled with the store  
12 computer system to effect a paperless delivery transaction. (Pocket size may  
here be taken as a terminal with a base perimeter of not more than twelve inches  
14 so as to fit in a typical side pocket of a jacket or the like having a depth of e.g.  
eight inches.)

16 This invention also relates generally to data collection and processing  
systems using portable, hand-held data terminals for collecting data, and for  
18 selectively processing and communicating collected data to other system  
elements. More particularly, the invention relates to collection apparatus of such  
20 hand-held data terminals. Typical collection processes may include reading  
data and manually keying in such read data. The present invention relates  
22 particularly to apparatus for reading data into the terminal. Known automated

reading processes are executed by apparatus which includes scanning readers,  
for example.

In efforts to adapt data collection terminals to a wider scope of uses,  
terminals with increased ruggedness over state of the art terminals are bringing  
advances to the art. However, the usefulness of the data collection terminals  
may also be increased by further reducing the weight and size of the data  
collection terminals to sizes and weights below the present lower limits of state  
of the art terminals. Typically a reduction in size might result in the elimination  
of at least some desirable features. The use of modular data collection  
terminals would support the reduction in non-essential features to achieve  
certain reduction in size and weight.

In the data capture field, there are many applications where hand-held data  
terminals should be of rugged construction so as to survive rough handling.  
Many operators are not inclined toward painstaking or precise manipulations.  
An example is in the use of RF data capture terminals on forklift trucks in  
factories and warehouses where items to be transported are identified by bar  
codes. Other examples are found in the fields of route delivery and direct store  
delivery where many items are handled and the terminal means automates the  
accounting function. Even in applications where bar code data is transmitted  
on-line to a central station, it may be desirable for hand-held terminals to be  
inserted into docking apparatus for the interchange of data signals e.g. the  
loading of scheduling information or the like into the terminal at the beginning of

a working shift. Further where terminal means has memory capacity for  
2 accumulating data during a delivery operation or the like, it may be desirable for  
such data to be transferred to a printer so that a hard copy may be produced. In  
4 cases where rechargeable batteries are used, the docking apparatus may  
provide for the recharging of such batteries at the same time as data  
6 communication is taking place.

It is conceived that it would be highly advantageous to provide a data  
8 capture system with docking apparatus adaptable to a wide range of terminal  
means, and which furthermore could be quickly and simply loaded in a relatively  
10 foolproof manner, and without requiring attention and care from operators  
engaged in physically demanding and arduous work routines. A docking  
12 apparatus would be desirable that completely avoids the use of mating pin and  
socket type electrical connections, and that does not rely on a specialized  
14 configuration of the terminal, e.g. the provision of an optical scanner tip which  
may be used for data communication. However, pin and socket type connectors  
16 may be utilized.

In connection with the use of portable data systems it is conceived that it  
18 would be highly advantageous to be able to readily upgrade a basic hand-held  
terminal to incorporate bar code scan type readers and various image readers  
20 as they are progressively improved and developed. A particular goal would be  
the implementation of the auxiliary image reader function in a rugged  
22 configuration free of moving parts. However, in the case of autofocus readers,

the current state of the art may require dynamic components for the sake of optimum compactness and economy.

#### SUMMARY OF THE INVENTION

Accordingly it is an object of the present invention to provide a plural module system configuration that is adaptable to a wide range of data capture applications while retaining pocket size and utilizing a core computer processor module of standard size and characteristics so as to achieve the economy of large scale production.

In a preferred embodiment the standardized computer processor module is provided with a multi-tasking operating system such that battery monitoring software and diagnostic routines will run at a fixed priority level at all times while a wide range of applications software can be run concurrently without jeopardizing the reliability of the system under extended portable operating conditions.

Preferably the standardized computer processor module is selectively associated with peripheral device shell configurations for adapting the system to specific applications. For example a shell configuration may include a scanner module for reading bar codes and a manual data entry and display means specifically tailored to a particular job such as package tracking, inventory, direct store delivery accounting, or the like. As a specific embodiment, the peripheral device shell may comprise a digitizer input tablet and display means which can receive handwritten input data and provide a desired confirming display. A

conversational mode may provide for multiple interpretive displays of successively lesser probability in response to an input character or word which is ambiguous with function key selection of the correct interpretation, or the like.

A voice input and/or voice synthesizer shell module is another exemplary embodiment. Again in a conversational mode, the module may repeat input words in synthesized speech and/or provide a visual display thereof whereupon actuation of a function button or the like may instruct the module to present a second most probable selection from its vocabulary.

The handwritten or voice input modules may include a learning program for progressively improving recognition of the individual user's characteristic handwritten or voice input. Physical objects related to a given user application may be assigned respective code words e.g. of eight bits length; thus in the case of a food service function, in a food selection mode, the writing of the letter "P" with a stylus on an input tablet or the spoken word "potato chip" may be stored as the ASCII code for the character P in a special food selection storage. A nonvolatile storage section would enable the translation of the "P" code in food selection mode into the string of characters "potato chips" on the display and/or produce the synthesized speech output "potato chips". In a conversational mode, if there were two or more P items, the shell module could in response to a "P" input, present on the display a listing of the P selections, e.g., as P1, P2, P3, etc., whereupon the user could enter with a stylus or the like the correct numeral "1", "2", "3", etc.

According to an exemplary embodiment, a peripheral device shell may provide a transparent tablet serving as data input and as a display window. A sonic wave digitizer arrangement for example may sense stylus (or finger) position on the tablet. The display may include a graphics liquid crystal display (LCD) behind the transparent tablet for defining a keyboard in a touch data entry mode, and for display of data supplied by touch entry, or by other means such as handwritten input, speech input, optical scanner input, and so on. Keyboard touch selection positions can be labeled by means of icons (pictorial images) where this is most effective. The pocket size unit may be of sealed construction so as to be ideal for meter reading, timber inventory, or any environmentally demanding application.

The computer processor module may be employed with peripheral devices such as printers, laser bar code readers, RF modules, smart card interface modules, disk systems, full travel keyboards, high resolution displays, local area network (LAN) interface modules, etc., and various such devices may be combined in a single self-contained battery powered hand-held unit.

It is also an object of the present invention to provide a terminal means which can be utilized by an individual at various locations for direct communication with another computer system for the purpose of carrying out desired individual transactions.



It is another object of the present invention to provide such a terminal which can be conveniently carried on the person of an individual, for example, in a shirt pocket.

A further object of the invention is to provide a terminal unit which is adapted to incorporate a means for reliably identifying an individual who uses the terminal and wherein the terminal facilitates each step in carrying out the desired transaction.

A feature of the invention resides in the provision of a terminal capable of removably receiving an information card with extensive memory capability and which, together with the terminal, can be held in one hand during entry of information concerning a transaction.

In accordance with a further feature, such a hand-held terminal system may incorporate means for two-way communication with a central computer system, e.g., via telephone lines or a radio frequency link.

In accordance with another feature, such a hand-held terminal system may be provided with a scanner for optically scanning visual information such as bar codes.

In accordance with another feature of the invention, such a hand-held terminal system may have dimensions of width and length comparable to a standard intelligent information card and of thickness to fit in the pocket, such as a shirt pocket.

In accordance with still another feature of the invention, such a terminal configuration is designed so as to be adaptable to a wide variety of applications without change in its basic housing configuration.

The PCT application Serial Number 90/0382, filed June 7, 1990, assigned to and owned by the assignee of the present application, the descriptive matter of which is incorporated herein by reference in its entirety, refers to such a modular hand-held unit and discloses a manner of attaching one functional module to another. The use of functional modules increases the scope of use of the basic data collection terminals by allowing the substitution of a most desirable feature in a particular application for another feature which may have become redundant. The eliminated feature may be least likely to be used in conjunction with the newly added feature. Without increase in size and weight of one type data collection terminal over another, respective functions may be adapted to specific situations. In certain applications, however, selected modules desirably include added features. The addition of such features in accordance with the invention is advantageously accomplished with a minimal size and weight change.

Hence, as contemplated, a laser scanner is added to a data collection terminal unit which typically features a radio frequency transceiver module. In accordance with particular features of the invention, a radio transceiver and a laser scanner are integrated into a single module with only a minimal increase in

volume over the volume of a radio transceiver module without the laser scanner  
2 unit.

According to another aspect of the invention, rotatively mounted scanning  
4 mirrors of a laser scanner are formed about magnetic poles of an armature of a  
motor for rotating the mirrors.

6 In accordance with another feature of the invention, electronic elements  
and physical elements for implementing functions of a laser scanner of the hand-  
8 held data collection terminal and electronic coupling circuits for interconnecting  
the laser scanner with the data collection terminal are disposed in interleaved  
10 relationship with electronic components for processing communications between  
a transceiver and the laser scanner.

12 Accordingly, it is an important object of the present invention to provide a  
portable data system wherein technologically advanced image reader devices  
14 can be readily accommodated.

16 In a presently preferred configuration particularly suited for forklift truck  
applications and the like, a portable data terminal with a rugged surface contact  
configuration accommodates supply of power by the vehicle when the terminal is  
18 placed in a vehicle mount; further, the terminal batteries may receive charge  
while the terminal is operating from the vehicle power so that full battery capacity  
20 is available when portable operation is required. However, other contact means  
might also be utilized.

In accordance with a further development of the invention, portable terminals, for example, may be quickly removed from the charging system by grasping of the terminal itself followed by a simple lifting extraction.

In accordance with an important aspect of the present invention, a docking apparatus removably receives portable data terminal and code reader means for purposes of data communication, e.g., with a host computer and/or for the recharging of rechargeable batteries. In one potential embodiment the terminal and reader means may have electrical contact pad means generally flush on their exterior. In such an embodiment, an abutting type engagement between the contact pad means and cooperating electrical contact means of the docking apparatus may be used for transmitting charging current such that the typical pin and socket type docking connections are entirely avoided.

In accordance with another aspect of the invention the same basic docking structure may be provided with greater or lesser numbers of contact positions. For example, one type of hand-held terminal intended for on-line RF communication with a host computer may have six contact pads for coupling with a local area network, and may have a nine position electrical connector for compatibility with an earlier type of interface system requiring interfitting of pin and socket connectors; another type of hand-held terminal designed for route accounting applications may have, e.g., twelve external contact pads and be intended for interfacing only with systems having provision for open abutment type interconnection.



The terminal and/or reader receptacle means is preferably arranged so that with the terminal or reader secured therein, each line of the display remains visually observable in a convenient orientation relative to a driver of a vehicle. Also all of the key positions of the keyboard are manually accessible, the legends on the keyboard having an orientation so as to be conveniently readable, e.g. by the driver of the vehicle. In particular the axis of each line of the display and of each row of key positions should be generally horizontal (rather than vertical) and the alphanumeric characters of the display and keyboard legends should be upright (rather than inverted) as viewed by the operator.

Also most preferably the terminal or reader can be inserted into the receptacle with one hand and is securely retained. Ideally the terminal or reader is automatically secured with a snap type action which is perceptible, e.g., audibly and tactually to the operator.

In some instances a resilient bias may serve to firmly position the terminal or reader for steady reliable electrical contact at each abutting type contact position in spite of vehicle jarring and vibration or the like. For enhanced security of retention with the docking apparatus, e.g. in mobile applications, the terminal or reader may be automatically affirmatively retained in its receptacle e.g. by means of a detent type action.

One exemplary embodiment of data capture terminal unit is provided with a plurality of electrically conductive pads generally coplanar with the external

surface of the housing. Such electrically conductive pads may be interconnected by internal circuitry to the connector elements of a D-style connector mounted upon the housing end cap such that recharge power and data communication pathways may be made through either or both of the connector means. The electrically conductive pads are positioned such that they may be engaged with mating elements having sufficient resilience to maintain stable electrical contact therebetween while the terminal is in a docking receptacle or the like.

According to another aspect of the invention, a laser light source may provide simultaneous illumination of a complete image line or a complete image column, or a substantial linear segment thereof, facilitating the achievement of a rugged image reader unit preferably without moving parts in the illumination system. In a further development a long range CCD image reader having auto-focus capabilities may be utilized with a fan beam for simultaneously illuminating a complete image line over a substantial range of distances.

Various other features and advantages of the data terminal in accordance with the invention will become apparent from the following detailed description, which may be best understood when read with reference to the appended drawings.

#### INCORPORATION BY REFERENCE

The descriptive matter of the above-referred to PCT International application PCT/US90/03282, filed June 7, 1990, as published under

International Publication No. WO 90/16033 on December 27, 1990, including  
2 forty-six pages of specification and nineteen sheets of drawings including FIGS.  
1 through 37 is hereby incorporated by reference.

4 FEATURES OF THE INCORPORATED PUBLISHED APPLICATION

The PCT International Publication No. WO 90/16033, which is  
6 incorporated herein by reference in its entirety, refers to a modular hand-held  
data collection unit and discloses a manner of attaching one functional module  
8 to another. The use of functional modules increases the scope of use of the  
basic data collection terminals by allowing the substitution of a most desirable  
10 feature in a particular application for another feature which may have become  
redundant. The eliminated feature may be least likely to be used in conjunction  
12 with the newly added feature. Without increase in size and weight of one type  
data collection terminal over another, respective functions may be adapted to  
14 specific situations. In certain applications, however, selected modules desirably  
include added features. The addition of such features in accordance with the  
16 invention is advantageously accomplished with a minimal size and weight  
change.

18 Hence, as contemplated, an image scanner utilizing an image sensor  
array may be incorporated in a module for a data collection terminal unit which  
20 may also include a radio frequency transceiver. In accordance with particular  
features of the invention, a radio transceiver and an automatic bar code reader  
22 with image sensor array and are integrated into a single module.

Various other features and advantages of the data terminal in accordance with the invention will become apparent from the following detailed description, which may be best understood when read with reference to the appended drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows a frontal view of a modular data terminal;

FIG. 2 is a side view of the data terminal shown in FIG. 1;

FIG. 3 is a side view of a related data collection terminal having a communications module without a laser scanner;

FIG. 4 is a side view of the data terminal shown in FIG. 1, showing somewhat schematically a data collection and communications module;

FIG. 5 is a sectional view, showing somewhat simplified a stacked arrangement of a radio, a communications interface main circuit board and a laser scanner assembly;

FIG. 6 is an exploded view of the data collection and communications module;

FIG. 7 is a partial plan view of the laser scanner assembly of FIG. 5;

FIG. 8 is a somewhat simplified sectional view of a motor assembly of the laser scanner assembly shown in FIG. 7;

FIG. 9 is a schematic plan view diagram of the motor assembly shown in section in FIG. 8;



FIG. 10 is a functional schematic diagram showing the manner in which the various elements of the data collection and communications module interact with each other;

FIG. 11 corresponds with the first figure of incorporated U.S. Patent 4,877,949;

FIG. 12 is a partial plan view of a laser scanner;

FIG. 13A shows an image sensor system utilizing a laser line type beam generator and an image focusing and sensing system for reading a reflected bar code image;

FIG. 13B shows a non-scanning laser illuminated bar code scanner for reading a reflected bar code image;

FIG. 13C shows the cross sectional shape of the beams produced by the laser sources of FIG. 13B;

FIG. 14 is a partial longitudinal sectional view of an image reader module similar to that of FIG. 16, but incorporating a transversely disposed antenna and a different optical port construction;

FIG. 15 is a partial plan view of the module of FIG. 14;

FIG. 16 shows an image reader module which may optionally use the image sensor system of FIG. 13A;

FIG. 17 is a plan view of the module case of the embodiment of FIG. 16, and illustrates an LED illumination system;

FIG. 18A is a cross sectional view of the module case taken generally  
2 along the line 15-15 of FIG. 17;

FIG. 18B is an end elevational view of the module case of FIG. 17;

4 FIG. 19 is a somewhat diagrammatic horizontal sectional view showing a  
different image reader system for incorporation in the reader modules herein  
6 disclosed;

FIG. 20 is a diagrammatic longitudinal sectional view of the system of  
8 FIG. 19;

FIG. 21 is a front view of the system of FIG. 19;

10 FIG. 22 is a diagrammatic illustration of the manner of applying a fan type  
laser line generator to the system of FIGS. 19, 20 and 21;

12 FIG. 23 is a diagrammatic illustration of a range and angle measurement  
system;

14 FIG. 24 is front elevational view of a conventional horizontally disposed  
bar code illustrating the impingement of a fan beam illuminating a bar code;

16 FIG. 25 is a diagrammatic illustration of a vertically and horizontally  
adjustable fan beam selector;

18 FIG. 26 is a diagrammatic illustration of the vertically and horizontally  
adjustable fan beam selector of FIG. 25 providing a fan beam output;

20 FIG. 27 is a somewhat diagrammatic perspective view illustrating the  
insertion of an intelligent information card into a receptacle of a terminal means

in accordance with the present invention while the terminal means is held by one  
2 hand;

FIG. 28 is a perspective view showing a terminal means in accordance  
4 with the present invention and showing an exemplary display including four  
single lines of characters and at the bottom Chinese characters occupying the  
6 height of two character lines of the display;

FIG. 29 illustrates a matrix of touch regions for a touch screen such as  
8 indicated in FIG. 28;

FIG. 30 is a schematic block diagram for illustrating an exemplary  
10 processing means occupying the interior of the terminal of FIGS. 27 and 28;

FIG. 31 is a somewhat diagrammatic perspective view showing a terminal  
12 which may be utilized particularly for selecting desired functions in a particular  
application of the terminal of FIGS. 27-30;

FIG. 32 shows the insertion of an intelligent information card into a  
14 receptacle of the terminal of FIG. 31 while the terminal is held by one hand;

FIG. 33 is a somewhat schematic block diagram for illustrating the  
16 electronic processing components which may be utilized with the embodiment of  
FIGS. 31 and 32;

FIG. 34 is a diagrammatic perspective view of a shirt pocket size terminal  
20 means in accordance with the present invention, including a scanner tip, and  
having portions broken away to show internal components;

FIG. 35 is a diagrammatic cross sectional view for indicating internal components of the terminal means of FIG. 34;

FIG. 36 is a diagrammatic view of a core processor module with touch screen type display and having length and width comparable to a standard credit or debit card and thickness to fit in a shirt pocket;

FIG. 37 is a diagrammatic perspective view showing an exemplary shell configuration for readily receiving the core processor module of FIG. 34, 35 and 36, to form a plural module terminal system, e.g., adapted for direct store delivery accounting;

FIG. 38 shows a store terminal device for coupling with the system of FIGS. 36 and 37;

FIG. 39 shows an exemplary coupling means for coupling the system of FIGS. 36 and 37 with the store terminal of FIG. 38;

FIG. 40 shows an exemplary plural module terminal system comprised of a shell portion having a processor and battery and also having optical indicia reader components and light output components, and shown with a display and manual data input module assembled in the shell receptacle; and

FIG. 41 shows another exemplary plural module terminal system comprising a shell portion having battery and light output components and a module assembled therewith containing optical indicia reader components.

**DETAILED DESCRIPTION OF THE INVENTION****2 1. Description of FIGS. 1-10**

Referring now to FIGS. 1 and 2, a data collection terminal unit, also  
referred to herein as data terminal, is designated generally by the numeral 10.  
As shown in FIG. 1, a frontal face 12 of an elongate housing 14 of a base  
module 16 of the data terminal 10 typically faces upward and is accessible to the  
user of the data terminal. The upward facing portion of the module 16 houses a  
keyboard module 17, including an alphanumerical keyboard 18 and a display  
screen 19. The display screen 19 is in a preferred embodiment described herein  
a 4-line by 16-character Reflective Super Twist Liquid Crystal Display (LCD). Of  
course, other display means may be used in its stead. The keyboard 18  
included a lower, standard numerical keyboard section 21, above which is  
disposed an alphabetical keyboard arrangement 22. An On-Off power key 23 is  
preferably placed in a leftmost position of an uppermost row on an uppermost  
row of five keys. The outermost keys 24 in a bottom row are configured as  
"CLEAR" and "ENTER", while the remaining four keys in the uppermost row are  
preferably configured as a set of four user-defined function keys 26.

At a bottom end 30 of the housing 14, there are located two connector  
plugs 31 and 32. The connectors 31 and 32 are protected by adjacent end and  
interleaved protrusions 36 of the housing 14, which protrusions extend  
somewhat past the connectors. A preferred embodiment of the data terminal 10  
is intended to withstand without damage a drop of about 1.2 meters to a solid

surface, such as concrete. The preferred connector 31 is an input-output port,  
as may be used for such data collection as bar code reading, for example. In  
such instance, the connector 31 is preferred to be a 9-pin D-subminiature  
connector with pins interfacing to typical 5 volt scanning peripherals. The  
connector 32 may be used for accessing external power sources or provide of  
combined power and data communication. A circular miniature DIN-type  
connector 32 may be used in the preferred embodiment. A top end 40 of the  
preferred embodiment of the base module 16 typically may not include  
connectors. An antenna 41 shown to extend above the top end 40 is further  
described in reference to FIG. 2. The described frontal, substantially  
rectangular configuration of the data collection terminal 10 has a length of  
substantially seven inches (Dimension A = 7 inches) and a width of  
approximately two and three quarter inches (Dimension B = 2-3/4"). The size is  
convenient to hold the terminal in one's hand, and as seen from FIG. 2, the  
thickness or depth of the data terminal 10 permits the terminal 10 to be carried  
about in a potential user's pocket.

FIG. 2 shows depth or thickness features of the data terminal 10. The  
base module 16 of the data terminal 10 with the described frontal face 12  
includes an elongate upper housing portion 43 which defines the longitudinal  
and lateral extent of the data terminal 10. Attached to the upper housing portion  
43 and disposed adjacent the bottom end 30 is a lower battery compartment 44.  
In the preferred embodiment, the battery compartment 44 is assembled as a

lower housing portion to the upper housing portion 43. Adjacent the top end 40 of the data terminal 10 a data collection and communications module 48 is attached to the lower edge of the upper housing portion 43. The antenna 41 as is typical for external antennas extends upward from the data collection and communications module 48 above the top end 40 of the data terminal 10.

One of the features of hand-held data terminals related to this invention and as disclosed in the PCT application PCT/US90/03282 incorporated herein by reference relates to the exchangeability of modules of different shape and varied function. It is of course desirable to have the various modules, though of different shape, substantially of the same size, such that the feel and handling of the family of data terminals 10 remain substantially identical regardless by what features a particular module may be distinguished over another data terminal 10. The data collection and communications module 48 in FIG 2. includes a radio 49 and laser scanning apparatus 50, the relative positions of which are best referred to in FIG. 5. Externally the presence of the radio module 49 is of course indicated by the presence of the antenna 41 in FIG. 2. The radio module may be a commercially available pretuned 1-watt (UHF) frequency modulated (FM) radio transceiver module, or any similar radio module, such as a Motorola P10tm radio model, for example.

In accordance herewith it is contemplated to provide the data collection and communications module 48 as a module which is capable of readily replacing another module, such as a radio communications module 51 which is



shown in FIG. 3, for example, and which does not include a combined radio and  
2 laser scanning function. Each of these interchangeable modules feature a quick  
exchange mounting mechanism, such as is more clearly illustrated with respect  
4 to FIG. 4. As shown in FIG. 4, the data collection and communications module  
48 is matched in a contour continuation along a juncture line 52 to the housing  
6 14 adjacent edge of the battery compartment 44 and along a longitudinal parting  
line 53 of the base module 16. The juncture line 52 defines a cavity within the  
8 base module 16 within which modules as the module 48 may be received. The  
module 48 features a plurality of laterally disposed latching hooks or latch hooks  
10 56 which become engaged by respective latching seats or latch seats 57  
disposed along the adjacent edge of the base module 16 when the module 48 is  
12 removed toward and into engagement with the adjacent edge and then toward  
the battery compartment 44, as shown by the arrow. Electrical communication is  
14 established via a power and communications connector 61 the pins of which  
engage a mating connector socket 62 within the base module 16. A set of  
16 screws 63 may be tightened through the battery compartment 44 into a set of  
threaded seats 64 disposed in the adjacent wall of the module 48 to securely  
18 retain the attached module as an integrated part of the data terminal 10. At the  
top end of the data terminal 10, a lip or extending stop edge 66 of the module 55  
20 engages a complementarily shaped seat 67 to securely interlock the data  
collection and communications module 48 with the base module 16.





FIGS. 2 and 3 depict a comparison of relative depths or thicknesses between the data collection and communications module 48 and the radio communications module 51. The radio communications module 51 is also shown equipped with a preferred hand strap 68 attached longitudinally to the rear of the data terminal 10. Though not presently contemplated for use on the data terminal 10 featuring the data collection and communications module 48, it is clearly possible to use the hand strap 68 on the data terminal 10 having the module 48. As seen in FIG. 3, the radio communications module 51 fits generally with its thickness into the contour of the housing of the data terminal 10. The additional laser scanning apparatus 50 does require an increased thickness or depth in the general contour of the housing 14. However, in accordance herewith, an increase in the thickness of the housing 14 has been minimized, as will become apparent from the further description of the improved arrangement of the laser scanning apparatus 50, but a necessary increase in the depth has been employed to increase the ease of manually holding the data terminal 10 during use. Either of the modules 48 to 51, when seated against the rear of the housing 14, blends with the contour of the housing along the line 52. FIG. 2 shows a thickness of the data terminal 10 at its bottom end of only about 1-1/2 inches (Dimension D), while the thickness at the top end 40 of the data terminal with the data collection and communications module 48 amounts to two inches (Dimension C1 = 2"). In FIG. 3, both top and bottom ends 40 and 30 of the data terminal 10 with the radio module 51 measure substantially the same



depth or thickness of about 1-1/2 inches (Dimension C2 = 1-1/2"). The increase  
in the thickness of the module 48 over that of the module 51 (Dimension E =  
1/2") is formed in a transition 69 which has been found to advantageously  
provide a resting ledge for the index finger of a user of the data terminal 10,  
providing added stability during use of the data terminal 10. With the index  
finger of the user resting against the transition or ledge 69, the thumb of the user  
is conveniently located along a lateral surface 70 of the module 48. A  
pushbutton 71 is disposed in the general area of the lateral surface 70 to be  
readily accessible for activation by the user's thumb. The pushbutton 71 is  
hence used to activate a laser scanning operation of the laser scanning  
apparatus 50. The pushbutton 71 may be duplicated in an identical location on  
the opposite lateral wall of the module 48. In this manner both left-handed and  
right-handed users of the data terminal 10 would be able to use the laser  
operation trigger pushbutton 71. The location of the pushbutton 71 in FIG. 2  
denotes both oppositely facing pushbutton locations on the opposite side walls  
of the module 48. The overall lengths of the modules 48 and 51 are  
substantially identical (Dimension F = 3.1/4") because of overall longitudinal  
restraints.

FIGS. 5 and 6 best illustrate the physical interrelationship between  
various elements of the radio 49 and the laser scanning apparatus 50 which  
results in the described minimal increase of the overall thickness of the data  
collection and communications module 48 over the radio module 51. The

module 48 is contained within a molded protective shell 75 of a high impact plastic material, preferably identical to the material employed for the housing 14. The outer contour of the shell 75 also blends into that of the housing 14, such that when edges 76 and 77 and the stop edge 66 are placed and locked against the respectively matching juncture lines 52 and the seat 67, the protective shell forms part of the housing 14. The edges 76 include the latch hooks 56 which lock the shell 75 to the housing 14. An apertured boss, such as indicated at 78 provides a mounting seat for the antenna 41. Interiorly of the shell 75 a plurality of spaced, internally threaded bosses 79 are disposed in a plane to support the mounting of a main circuit board 82, which is also referred to as an analog board 82.

The analog board 82 is a multi-use element, in that it is first of all a circuit board. The circuit board 82 is in particular a four-layer circuit board, having conductive patterns disposed on both major outer surfaces 83 and 84, the conductive patterns including designate sites for mounting electronic components to both sides of the circuit board. Two inner conductive planes provide ground and interconnection planes for the components on the respective outer surfaces of the circuit board 82. The ground plane within the circuit board 82 substantially isolates electrical radio noise from interfering with the laser scanning components and to minimize such radio noise from being emitted from the shell 75.

To the surface 84 of the main circuit board 82 there is mounted a laser scanner submodule 86. The laser scanner submodule 86 includes a mounting frame 87, preferably a molded structure of a high impact plastic. A laser diode 88 is mounted to a support seat 89 of the mounting frame 87. The laser diode is of cylindrical shape, approximately 1/2 of an inch in diameter and about 3/4 of an inch long. The laser diode 88 is a known commercially available element, such as under the designation TOLD 9211 from Toshiba Electric, for example. The laser diode is provided as a fully assembled unit including collimating optics having a lens window 90 through which a collimated laser beam is emitted. The preferred laser diode 88 is of "InGaAlP" material, a known laser material which emits light in the humanly perceivable wavelength range of 670 nanometers. The emitted light is perceived as ruby red, giving the operator of the laser scanner an indication of the operability of the laser and permitting the laser light to be visually "aimed" against indicia such as a bar code to be read. A scanning mirror assembly 92 is placed adjacent the path of the emitted laser beam, such that in a plan view a regular polygon 93 of highly polished mirrors 94 is disposed in the plane of the laser beam emitted from the window 90. The mirrors 94 form a cylinder having a sectional shape of a regular polygon. In the preferred embodiment a total of ten mirrors 94 are evenly spaced about the periphery of the right cylinder. The laser beam impinges on a primary reflector mirror 95 which is typically held in a seat 96 of the frame 87. The scanning mirror assembly 92 is a circuit board mounted assembly of stepping motor assembly

98. The right cylinder appearing in plan view as a regular polygon 93 of the  
mirrors 94 constitutes an armature of the motor assembly 98. The mirrors 94 are  
formed in the peripheral wall of the armature of the motor assembly 98. A motor  
circuit board 99 supports a spindle 102 of the armature 93. The motor circuit  
board 99 also supports electronic driver components of the motor assembly 98.  
The scanning mirror assembly 92 is mounted to the frame 87. A cut-out 104 in  
the circuit board 99 provides clearance between the board 99 and the laser  
diode 88, such that the mirrors 94 are disposed in the emission plane of the  
laser diode 88.

An optical analog circuit board 105 is mounted against the frame 87  
across from the main circuit board 82 and fastened with typical mounting screws  
106 to the frame 87. A typical circuit board connector pin arrangement, such as  
is shown at 108 may be connected to a typical flat cable 109 to electrically  
couple the analog circuit board 105 to the main circuit board 82 and to the  
scanning mirror assembly 92. The circuit board 105 includes circuit elements for  
receiving and amplifying optical signals which represent reflected signals as a  
result of the outgoing laser beam from the laser diode 88. The circuit elements  
include such typical elements as photo diodes which are integrated into  
receiving optics 112 mounted to the circuit board 105.

Mounted to the surface 83 of the main surface board 82 is a radio support  
frame 115. The radio support frame 115 is a U-shaped frame which is mounted  
peripherally about the circuit board 82 extending upward from its surface 83.

Formed tongues 116 of the support frame 115 are insertible into apertures 117  
2 of the circuit board 82 to fasten the frame 115 to the circuit board. The frame  
115 has a predetermined height between a lower edge 118 and an upper edge  
4 119. Apertured mounting lugs 121 disposed at the upper edge 119 are adapted  
to receive the threaded fasteners 106. The radio 49 is mounted on a circuit  
6 board 122. The circuit board 122 is attached, such as by the fasteners 106, to  
the lugs 121 of the support frame 115, the height of the support frame 115  
8 spacing the main circuit board 82 and the radio circuit board 122 to  
accommodate the components on both boards. The support frame in  
10 conjunction with the ground plane of the circuit board 82 also forms a radio  
frequency emission cage about the components of the radio circuit board 122,  
12 containing radio frequency (RE) emissions in accordance with regulations. The  
circuit board 122 may in itself contain RF shielding toward the tip of the formed  
14 cage, or separate shielding such as an additional board having a ground plane  
may be added.

16 A circuit board connector pin arrangement 125 receives a typical circuit  
board connector strip 126 of a circuit routing board 127. The circuit routing  
18 board 127 routes power and communicative interconnections between the main  
circuit board 82 and the base module 16. A conductive ground plane 128 of the  
20 routing board 127 may preferably be coupled to the support frame 115 to  
complete the RF cage in conjunction with the support frame 115 and the ground  
22 plane of the main circuit board 82.

The assembly of the described elements of the main circuit board 82, the laser scanner assembly 86 and the radio 49 into the housing shell 75 spaces the elements tightly, placing the plane of the laser beam and the receiving optics 112 of the laser scanner analog circuit board 105 adjacent a scanning window 131 of the shell 75. The scanning laser beam and its reflection pass through the window in the outgoing and incoming directions, respectively. Spacing the described components at minimum distances adjacent one another as shown in the sectional view of FIG. 5, for example, is made possible by a cutout 132 in the main circuit board 82 to accommodate an upper portion of the laser diode 88. It has been found that the cutout 132 in the main circuit board 82 and hence in its ground plane does not adversely affect RF shielding of emissions from the radio 49. Further in reference to the main circuit board 82 as shown in FIG. 6, the circuit board 82 includes on opposite edges 136 and 137 electrical actuator switches 138. The switches 138 are the electrical components which in conjunction with the external element of the pushbutton 71, typically a molded rubber-part, form the pushbutton 71. The external portion of the pushbutton 71 is disposed in the shell 75 to become aligned with the electrical actuator switches 138 when the main circuit board 82 is assembled into the shell 75 as shown in FIG. 5, for example.

FIG. 7 is a simplified top view of the laser scanner assembly 86 to show the path of the laser beam emitted from the laser diode 88, as shown at 140. The laser beam 140 impinges against the primary reflector mirror 95 and is

reflected at 142 against the rotating polygon of preferably ten mirrors 94. The  
armature 93 rotates during the scanning process in the direction of arrow 143,  
such that the laser beam reflected from the mirrors 94 scans at 144 in a direction  
from left to right of an operator holding the data terminal 10. Left and right  
scanning window edges 146 and 147, respectively, cut off the laser beam to the  
far left and right and limit the scanning angle to a reasonable deflection from a  
centerline of the data terminal 10. The optimum scanning angle may be altered  
by relocating the window edges 146 and 147 accordingly. The laser beam,  
when reflected from an impinged on surface 149 into the receiving optics 112;  
would be modulated in accordance to reflection patterns on such reflected  
surface 149, such as the dark and light alternating regions of a bar code.

FIG. 8 is a cross sectional view through the stepping motor assembly 98  
which is somewhat simplified for the sake of clarity. The motor circuit board 99  
supports magnetic field coils 151, of which there may be three equally spaced  
coils, as in a preferred example. The coils 151 lie in the plane of the motor  
circuit board 99 and direct a magnetic field substantially perpendicularly thereto  
out of the plane of the circuit board 99. The coils 151 are electrically coupled to  
electronic driver elements (not shown) which are preferably also disposed  
adjacent the coils 151 on the motor circuit board 99. The main body of the  
armature 93 is of non-magnetic material, such as aluminum. However, a  
magnetized permanent magnet element 153 is disposed in a central recess 154  
of the armature 93. The armature 93 is rotatably supported by the spindle or



shaft 102 which may be mounted for rotation in a bearing 156 disposed on the surface of the motor circuit board 99. Alternately, the spindle might be fixedly mounted to extend from the motor circuit board 99, such that the bearing 156 would reside between the spindle and the armature. A circular plate 157 of a magnetically conductive material is disposed below the circuit board 99 to serve as a magnetic flux shunt and provide a magnetic return path for the magnetic flux lines generated by the coils 151.

FIG. 9 showing a schematic plan view of the armature 93 and the field coils 151. The magnet element 153 of the armature 93 has a plurality of alternately oriented peripherally spaced magnetic polepieces 161 which are in a preferred embodiment part of the single ceramic type magnet disc 153. Within each of the coils 151, there may be located a hall effect sensor device 162. The hall effect sensors 162 detect from the magnetic field the current position of the armature or rotor 93 to control the switching of the drive current through the coils 151. In the stepping motor art there are various known ways of switching coils and of overdriving in accordance with the position of the rotor 93 to achieve a desirable drive pattern of the rotor. In the present embodiment of the invention, a substantially uniform scan rate is of course desirable, though the armature or rotor 93 is driven through the stepping sequence of the motor assembly 98. It should be understood that the use of hall effect devices to determine the position of the armature 93 is but one known manner for controlling the speed of rotation and the position of the armature. It is also possible to use opto-electronic

encoding techniques to achieve substantially similar position recognition and to  
2 control the speed of rotation of the armature 93. It is to be realized that the  
flattened structure of the motor assembly 98 resulting from the folding back of  
4 the mirrors 94 on the armature 93 is of significance in containing the radio 49  
and the laser scanner 50 within the shell 75 of the preferred size as described  
6 herein.

Reference to the schematic diagram in FIG. 10 shows major functional  
8 elements of the described data collection and communications module 49. The  
functional representation of the laser scanning assembly 86, referred to in FIG.  
10 as laser module 86 is coupled with four connections to a scan bus 171 on the  
main circuit board 82. The electronic circuits in the laser module for driving the  
12 stepping motor and for amplifying reflected signals is a commercially available  
configuration. In the preferred embodiment, the circuits of the laser module 86  
14 have been obtained from Optoelectronics Co. Ltd. in Japan. Connections for  
communicating signals between the laser module 86 and a microprocessor  
16 (CPU) 174 of the base module 16 include RENABLE, DATA, TIMING (SOS), and  
ground (GND). RENABLE activates the laser module 86 upon one of the  
18 pushbuttons 71 being closed, as represented by SW1 and SW2 on the main  
circuit board 82. Closing of either of the pushbuttons 71 is recognized by the  
20 CPU 174 of the base module 16. The CPU switches the RENABLE connection  
to a high, which powers up the laser scanner assembly 86. VCC is a typical  
22 power input, while the laser diode is driven through a DC to DC converter

"51953", identified by numeral 176. When the motor 98 has come to speed the laser diode is turned on, and the laser module d86 sends a signal via TIMING (SOS) to the CPU 174. The TIMING signal frames the data and alerts the CPU that data are forthcoming. Data are transmitted to the CPU via the DATA line and the scan bus 171. It should be noted that the scan bus 171 is coupled via the routing board 127 to the CPU 174 of the base module 15, and all other signal and power lines are simply routed through the routing board 127 between the main circuit board 82 and the base module 16. There is no further manipulation of data or signals between the CPU and the laser module 86 on the main circuit board. On the other hand, the main circuit board 82 performs various functions relating to the control of radio communication between the CPU 174 and the radio or transceiver board 49. It should be noted that not all possible control leads to the radio 49 are connected to the CPU 174 or to the main circuit board 82, though it is conceivable that additional functions may be implemented and connected in variations of the preferred embodiment with respect to which the invention is described. Functions relating in particular to the control of the radio 49 and particularly to the frequency control in digital data transmission are discussed in related U.S. application Serial No. 07/467,096, filed January 18, 1990, by S.E. Koenck and R.L. Mahany, assigned to the assignee of the present application, the disclosure of which in its entirety is incorporated herein by reference. Thus, as is apparent from FIG. 10, the TRANSCEIVER INTERFACE function represented by a circuit element 177 is a

communications interface for between the radio 49 and the CPU 174. The  
circuit element 177 activates power to the radio 49 and controls transmission  
and reception signals, such as indicated by TX MOD and DISCR OUT. The  
circuit element 177 is driven by an on board clock timed by a 4MHZ crystal 179.  
A buzzer circuit 181 is amplified using on-board power of the main circuit board  
82. It should be realized that not all connections from any commercially  
available radio 49 and the main circuit board may be used. Various types of  
radios are known, of which certain radios may function on more than one  
frequency or a radio type referred to as spread spectrum radio may require  
various controls. It is contemplated that such radios referred to as spread  
spectrum radios may be used in conjunction with and as part of the invention  
described herein. The descriptive matter of U.S. patent application Serial No.  
07/660,615, filed February 15, 1991, by S.E. Koenck et al., the application being  
assigned to the assignee of the present application, is being incorporated herein  
by reference. Such patent application refers to advantages of adapting modules  
to function with different radios. It appears from the above disclosure herein that  
the present invention may be adapted to function with a number of such different  
types of radios.

Various other changes and modifications in the structure of the described  
embodiment are possible without departing from the spirit and scope of the  
invention as set forth in the claims.



## 2. Description of FIG. 11

FIG. 11 illustrates a preferred instant bar code reader system for extending the versatility of a commercial bar code reader such as shown in U.S. Pat No. 4,570,057. Component 3510, FIG. 11, may represent a control and processing means for the system and may include a central processing unit, memory units and analog to digital conversion channels.

The central processing unit and associated memory form the main control portion of the system. The other functional blocks of FIG. 11 may be inputs or outputs with respect to the central processing unit.

The central processing unit may be a microprocessor that executes the program to control the operation of the reader. The microprocessor acts as a microcontroller with the capability of sensing and controlling the functional elements of the bar code reader, and decoding the bar code as supplied from a code image sensor means 3511.

Where the reader is coupled on line with a host computer system, (for example by a host connection means in the form of a flexible cable), the decoded bar signal is transmitted to the host under the control of the central processing unit. The microprocessor is capable of static operation with shut-down for power conservation.

Wake-up of the processor will occur when an operator actuates a scan switch 3512.

An electrically erasable read only memory of component 3510 may be utilized to store parameters and special modifiable decoding sequences for the bar code reader operation. Examples of these parameters would be label code, and input/output speed and control format.

Component 3510 may also include a random access memory for data collection,  
2 decoding work space and buffer storage of the decoded label data for transmission to a  
host computer, for example. The random access memory can be internal to the  
4 microprocessor chip or reside on a data bus.

The analog/digital channels are for receiving the bar code signals generated by  
6 the bar code image sensor mean 3511 and for other purposes as will be hereafter  
explained.

8 The image sensor means 3511 may, for example, include a photosensor array  
indicated diagrammatically at 3513 having a one dimensional linear array of  
10 photodiodes for detecting the bar code reflection image. To read labels with bar code  
lengths of greater than seven inches with high resolution requires that the array have  
12 relatively high resolution. By way of example, the array 3513 may comprise five  
thousand photodiode circuits (5,000 pixels) and provide approximately three  
14 photodiode circuits (3 pixels) for each five mils (0.005 inch) of a bar code length. (Each  
pixel of array 3513 may have a length of about seven microns.) A charge coupled  
16 device (CCD) shift register may be arranged to receive bar code signal elements from  
the respective photodiode circuits after a suitable integration interval. Once the bar  
18 code signal elements have been transferred to the shift register, the signal elements  
are retained independently of further exposure of the photodiodes to reflected light from  
20 the bar code.

In the embodiment of FIG. 11, an intensity sensor 3514 is provided and may  
22 comprise a photodiode that will determine the relative amount of light exposure of the

photosensor array 3513. If component 3510 operates at sufficiently high speed, the  
2 signal from the intensity sensor 3514 may be supplied exclusively to component 3510  
via an analog/digital channel so that the control and processing means can determine  
4 the optimum point for transfer of the bar code image signals to the shift register.

In a presently preferred implementation, however, the intensity sensor means  
6 3514 is directly coupled with the hardware control circuits of the flashable illuminator  
means and of the bar code image sensor means, and this is indicated by dash lines L1  
8 and L2 in FIG. 11; in this case, line L is used only so that the processor component  
3510 is advised that a flash has actually occurred. In a preferred embodiment wherein  
10 a flashable illuminator 3515 is driven by capacitor discharge current, a component  
3516 may effect interruption of the flow of current from the capacitor based directly on  
12 the signal supplied via L1 from intensity sensor 3514. In this way, energy is conserved,  
and recharging of the capacitor speeded up. Component 3516 may comprise a flash  
14 current interrupter switch means, e.g. a solid state switch which is controlled to interrupt  
discharge of the capacitor of high voltage generation unit 3517 and thus to terminate  
16 the flash of light from the flashable illuminator 3515 when intensity sensor 3514  
indicates that adequate reflected light has been received from a bar code.

18 FIG. 11 also indicates an input/output buffer component 35121 for  
coupling the control and processing means 3510 with a host processor or the  
20 like. A connection means 35122 may directly receive a host processor so that  
the host processor housing is physically attached with the reader housing. As  
22 another example, connection means 35122 may comprise a cable containing six

conductors. Preferably, such a cable would be detachable at the reader. In this  
2 second example, all needed voltages may be generated in the reader from plus  
five volts supplied by two of the six conductors (+5 V, GND). The other four  
4 signal lines of the cable are preferably independently programmable as inputs or  
outputs. By way of example, the host processor may be part of a held computer  
6 such as shown in U.S. Pat. Nos. 4,455,523 and 4,553,081. The rechargeable  
batteries of the portable computer may supply all needed power to the reader  
8 unit of the present invention. In the second example, a host computer unit can  
be carried in a belt holster for example during extended use of the reader unit of  
10 the present invention.

### 3. Description of FIGS. 12, 13A, 13B, and 13C

12 FIG. 12 is a view similar to FIG. 7 of U.S. application Serial No.  
07/881,096 (filed May 11, 1992, now abandoned), but showing the use of two  
14 laser diode sources Z88-1 and Z88-2. FIG. 12 is generated by shifting parts 88,  
93, and 95 in FIG. 7 of U.S. application Serial No. 07/881,096 (filed May 11,  
16 1992, now abandoned) to the right so that the center of rotation of rotor Z93  
coincides with axis Z148 lying centrally of reader window Z131. Then parts Z88-  
18 1 and Z95-1 as so located relative to central axis Z148, are replicated to the left  
of axis Z148 as parts Z88-2 and Z95-2. The frame 87 (as illustrated in the sixth  
20 figure of U.S. application Serial No. 07/881,096, filed May 11, 1992, now  
abandoned) is now constructed symmetrically to accommodate the two laser  
22 diode sources Z88-1 and Z88-2.



FIG. 13A shows the use of two line type laser sources Z201, Z203, and

2 Z202, Z204, each illuminating a total field of view Z205 in common, in which  
case moving parts such as rotor Z93 are entirely eliminated. The image sensor  
4 array and optics system 112 (as illustrated by the fifth figure of U.S. application  
Serial No. 07/881,096, filed May 11, 1992, now abandoned) 12, including optics  
6 112A and image type photosensor array 112B, e.g., a CCD image sensor array,  
is located within the dimension E, (as illustrated by the second figure of U.S.  
8 application Serial No. 07/881,096, filed May 11, 1992, now abandoned), below  
motor circuit board 99 for the embodiments illustrated by figures one through ten  
10 and eleven in U.S. application Serial No. 07/881,096, filed May 11, 1992, now  
abandoned.

12 FIG. 13B shows certain components of a non-scanning laser illuminated  
bar code scanner wherein two solid state laser sources Z1201, Z1203 and  
14 Z1202, Z1204 are placed off axis from the centerline of the CCD optical path.  
The sensing device does not require a folded light path. Since mirrors are not  
16 required sensitivity is increased up to five percent per optical interface removed.  
The half power radiation line for the solid state laser sources (Z1201, Z1203 and  
18 Z1202, Z1204), after passing through the dispersive optics (Z1203, Z1204)  
normally have an elliptical cross-sectional shape. When the ellipse is altered by  
20 non-axisymmetric propagation it is fanned out into a distorted pattern which no  
longer fully resembles an ellipse (FIG. 13C). This may be corrected by using  
22 two laser sources with outputs which overlap a target bar code. Such a

configuration acts to partially compensate for this pattern distortion. Further compensation may be achieved by utilizing a flash A/D converter and applying conventional digital high pass filtering techniques on the converted data to eliminate the residual effect on uneven illumination. The two laser sources are preferably high powered devices which are pulsed rather than used on a continuous basis. This provides intense illumination for a brief period of time. In such an embodiment the high voltages required by a Xenon flash are not necessary.

For the embodiment of FIGS. 13A and 13B, the mounting frame Z87 and the motor circuit board Z99 may be omitted, and the image reader circuitry associated with system Z112 and laser diodes Z201, Z202 may be placed at side Z84 of the main circuit board Z82. The laser sources Z201 and Z202 may be accommodated by cutouts such as 132 (as illustrated by the sixth figure of U.S. application Serial No. 07/881,096, filed May 11, 1992, now abandoned) to minimize any required extra thickness E, (see FIG. 2 of 07/881,096), of the image reader/RF module containing the components Z112 and Z201-Z204 of FIGS. 13A and 13B.

#### 4. Description of FIGS. 16-18B

FIGS. 16-18B illustrate an image reader/RF module for assembly with the base module 16 (as illustrated in figures 1 through 10 of 07/881,096), and which may be readily modified to form the system of FIG. 13A with no moving parts.



FIGS. 16-18B show an image reader/RF module Z210 which is interchangeable with module 48 (of the fourth figure of 07/881,096) and Module 51 (of the third figure of 07/881,096) with respect to base module 16. A terminal housing including base module housing 14 and module shell 214 has the overall dimensions A, B, D and Cl as given with reference to the first and second figures of 07/881,096 (i.e. A is about seven inches, e.g. 6.875 inches or 17.46 centimeters; B is about two and three-fourths inches, e.g., 2.625 inches or 6.68 centimeters; D is about one and one-half inches, e.g. 1.25 inches 3.18 centimeters; and Cl is about two inches or about five centimeters). The image reader module Z210 is provided with an edge face Z214A (FIG. 18B), mating with edge faces such as 52 and 53 of the base module 16 in the same way as described for the module 48 of the second figure of 07/881,096. A downwardly protruding wall portion Z214B advantageously provides a gripping margin for the index finger of a user of the data terminal providing secure support for the terminal even in the absence of a hand strap such as 68 (as illustrated in the third figure of 07/881,096).

The module Z210 is shown as being provided with latch hooks Z216 (FIG. 18A), for interengaging with respective latch seats 57 (FIG. 4 of 07/881,096), as with modules 48 and 51. Module Z210 is also equipped with a stop edge Z214C, (FIG. 18A), with a recess Z217 for interlocking with a projection Z218 of the seat 67, (FIG. 4 of 07/881,096), as the module Z210 is moved longitudinally into its final position. Threaded seats are indicated at Z219, (FIG. 18B), for

receiving screws 63, (FIG. 4 of 07/881,096), so as to fasten module Z210 as a  
2 fixed part of the data terminal.

During longitudinal movement of module Z210 into its final assembled  
4 position, the pins of connector Z222 interengage with the receiving connector  
62, (FIG. 4 of 07/881,096). The relative longitudinal positions of latch parts  
6 (216, 57) assure that the pins of connector Z222 are moved upwardly to a  
position just in front of and aligned with connector 62 before the longitudinal  
8 movement can begin. The levels of mating edges (53, 214D) of the base  
module 16 and of the module Z210 assure that the pins of connector Z222 must  
10 be at the proper level during longitudinal movement as permitted by the  
interfitting configurations of latch parts (Z216, 57).

12 In the implementation of image scan/RF module Z210 shown in FIG. 16, a  
main analog board Z228 underlies a radio subassembly Z230 including an RF  
14 board Z234. The main analog board Z228 essentially corresponds with main  
analog board 82, and the RF board Z234 is essentially the same as RF board  
16 122 of the previous embodiment. An open rectangular metal shielding frame  
Z236 surrounds the RF components. The RF board Z234 may in itself contain  
18 RF shielding toward its upper surface, or separate shielding such as an  
additional board having a ground plane may be provided immediately above the  
20 RF board Z234 as shown at 123, (FIG. 6 of 07/881,096).



In an embodiment where the RF transmitter is not active at the same time as the scanner subassembly, no special RF shielding was included with the RF board Z234.

In a specific implementation, the shielding frame Z236 is provided with projecting tabs which are inserted into receiving slots of the analog board Z228 and soldered in place so as to be directly electrically connected with the inner ground plane of the analog board Z228 (in the same way as for tongues 116 and apertures 117 of the sixth figure of 07/881,096).

FIG. 18A shows a cross section of the module shell Z214 taken along line 15-15 of FIG. 17. This Figure shows integral rib means Z251 which also appears in FIGS. 16 and 17, and which adjoins a through-aperture Z252 accommodating the threaded end of antenna Z253. A thin metal plate Z254 fits into the space Z255 and is captured therein and prevented from rotation when the antenna is threadedly engaged therewith.

A boss Z260, FIG. 18A, integral with the shell 214 has a threaded insert for use in securing the RF assembly Z230 to the shell. A transverse rib Z263, (FIG. 18B), extends near edge face Z214A and bosses Z264 for receiving threaded seats Z219.

Referring to FIG. 18A, the shell Z214 has thickened end wall portions Z270 and Z271 with respective sets of cylindrical bores Z281 for receiving respective light emitting diode units such as Z291, (FIG. 16), for directing

illuminating beams along respective beam axes Z301-Z306, (FIG. 17), toward an  
2 image plane Z307.

Centrally of the shell frontal wall there is an inwardly extending boss Z310  
4 having a cylindrical chamber Z312 which opens through the front wall and  
accommodates insertion from the exterior of an optics subassembly such as  
6 diagrammatically indicated at Z314, FIG. 16. The optics Z314 collects reflected  
light from a bar code or the like at the image plane Z307 via an entrance portion  
8 which communicates with optics chamber Z312 and which is diagrammatically  
indicated at Z312A in FIG. 17. A reduced diameter aperture Z318 of boss Z310  
10 accommodates the passage of the focused reflected image along an axis Z320.  
A reflecting mirror Z322 secured at a seat Z324 formed by shell Z214 redirects  
12 the reflected bar code image to an image sensor Z326 which is mechanically  
and electrically connected to the image reader board Z266.

14 In the exemplary embodiment, the optics Z314 focuses a bar code image  
onto image sensor Z326 for positions of the bar code along optical axis Z330,  
16 (FIG. 16), which are beyond the end of the antenna Z253. In this way a simple  
optical arrangement can be utilized, even an optical arrangement with minimal  
18 depth of field of approximately one inch.

In the exemplary embodiment, the lens system Z314 was from a  
20 commercial CCD reader of Norand Corporation which utilized a folded optical  
path generally as shown in U.S. Patent 4,894,523 issued January 16, 1990. It

was possible to eliminate two reflectory mirrors of the folded optical path by placing the bar code sensing region beyond the antenna.

In the exemplary implementation it was found that a substantially more uniform illumination of a bar code could be obtained at an operating range beyond a three inch antenna by adjusting the axes Z301-Z306 somewhat in comparison to directions parallel to the optical axis Z330 as indicated in FIG. 16, such that the axes Z301-Z306 of the beams intersect the image plane Z307 at uniformly spaced points.

## 5. Description of FIGS. 14 and 15

FIGS. 14-15 illustrate a further image reader/RF module for assembly with the base module 16 of the first through tenth figures of 07/881,096, and which may be readily incorporate the laser reader system of FIG. 13A with no moving parts.

FIGS. 14 and 15 show the further image reader/RF module Z410 which is interchangeable with modules 48, 51, and 210. Elements Z414, Z414A, Z414B, Z414C, Z414D, Z416, Z417, Z422, Z428, Z430, Z434, Z436, and Z491 of FIGS. 14 and 15 substantially conform with elements Z214, Z214A, Z214B, Z214C, Z214D, Z216, Z217, Z222, Z228, Z230, Z234, Z236 and Z291 of FIGS. 16-18B, so that the description of these elements will be understood by reference to the description of FIGS. 16-18B.

As seen in FIG. 14, housing Z414 is provided with an outwardly protruding seat; Z414E which receives a snap-on cowl piece Z510 which serves

to retain an optical window Z531 covering an elongated generally rectangular opening at the front housing Z414.

As shown in FIGS. 14 and 15, the module Z410 has a transverse extending antenna Z546 housed within a dielectric cover Z548 completely within the confines of the length of housing Z14 with cowl Z510, and within the width dimension of housing Z14. The antenna may be a helical wound wire type, and may be carried by a fitting Z510 having an enlarged base Z550A for coupling with the RF circuits Z430.

#### 6. Description of FIGS. 19-22

FIGS. 19-22 show a reflected image reader submodule which may be used in any of the embodiments disclosed in US application Serial No. 07/881,096 such as those of the first through eleventh and the thirteenth through eighteenth figures of Serial No. 07/881,096, and the foregoing embodiments taken with FIG. 13A. Coplanar solid state light sources, including laser diodes Z210, Z202, and cylindrical lenses Z203, Z204, similar to those shown in FIG. 13A may also be included with submodule Z600, for example at Z601, Z602 outside the margins Z603, Z604 of the collecting zone for the reflected light image, or the submodule may operate from ambient light, or from light from an auxiliary spot-light like the light source on a vehicle and separate from the hand-held bar code reader of any of FIGS. 1-18 of 07/881,096, equipped with the submodule 600.



In the submodule Z600, the reflected image impinges on a reflecting mirror surface Z610A of a segmental spherical aluminum mirror Z610 whose height corresponds to the height of module Z600 and may correspond generally with height E, (FIG. 2 of 07/881,096). Mirror Z610A reflects the incident image to a surface mirror region Z620A of a cover glass Z620. The image is again reflected and is then focused by lens assembly Z630 onto an photodetector image array Z640. A linear actuator Z650, FIG. 20, may be coupled with the lens assembly Z630 and control the axial position thereof for optimum focus of the information image onto array Z640, e.g., as in referenced U.S. Patent 4,877,949, issued Oct. 31, 1989.

The aluminum spherical mirror Z610 may function not only as an optical element, but also as a structural element for supporting the lens assembly Z630 and autofocus linear actuator Z650. The use of large mirror surface Z610A as seen in FIG. 19 allows the size of the subsequent optical string to be reduced since the lenses Z630 (an achromatic doublet has been indicated) are not relied upon as the principal light gathering structure.

A preferred approach to integrating a fan beam generator with the photodetector submodule Z600 is illustrated in FIG. 22.

In FIG. 22, the housing of the module Z600 is shown with light proof walls Z660 and with the window Z620 opaque at Z661 in front of mirror surface Z620A. Then a mirror surface is provided at Z670 for transmitting a vertically

incident fan-shaped laser beam Z671 into a fan beam plane at Z672 which is  
2 coplanar with the optical axis Z674, (FIG. 19).

FIG. 22 shows a laser diode source Z680, spreading optics Z681 and a  
4 right angle prism or mirror surface Z682 for redirecting a horizontal fan-shaped  
laser beam at Z683, these components Z680-Z682 being carried at a top wall  
6 Z660A of submodule Z600.

The configuration of the fan beam with central axis Z672 is indicated by  
8 marginal rays Z672A and Z672B in FIG. 19, and an exemplary image plane is  
indicated at Z690 for a given axial position of optics Z630.

## 10 7. Discussion of FIGS. 12-18B

In housing a photosensor image array such as a CCD linear multi-element  
12 array for component 112, (FIG. 5 of 07/881,096), the integration time of the  
sensor array is synchronized to the scan rate of the laser beam (FIG. 7 of  
14 07/881,096) or laser beams (FIG. 12) so that each pixel of the array would  
receive an equal amount of light with the beam scanning a uniformly reflecting  
surface. In reading a bar code, after one or more complete scans of the bar  
16 code by the laser beam, the image data is read out of the array such that each  
18 pixel of the array is coupled with the laser beam or beams an equal number of  
times before read out, i.e., receives an equal number of exposures to reflected  
20 light from the laser beam or beams.

The problem of synchronization does not arise when a laser line projector  
22 or laser line projectors, as in FIG. 13A, simultaneously illuminate all elements of

the bar code. The illuminated complete bar code is then imaged at all of the  
2 elements of the sensor array at the same time, so that the integration time can  
be selected solely from the standpoint of formation of an optimum output signal  
4 from the image array.

In FIG. 13A, the output from each laser diode has a beam cross section  
6 which is of an elongated elliptical configuration. The semi-major axis of the  
beam cross section is oriented so that as it strikes the respective cylindrical lens  
8 Z203, Z204, the elongated nature of the cross section is enhanced and it  
spreads out to a length preferably to cover a complete line of a bar code. If  
10 some collimation is provided in the plane of the semi-minor axis, then the  
elliptical cross section becomes an approximation of a line.

It will be understood that the line type solid state laser light sources Z201,  
12 Z203, Z202, Z204 of FIG. 13A are readily substituted for the LED arrays 291  
(FIG. 14 of 07/881,096) or Z491, FIGS. 14-15.

In an embodiment according to FIGS. 16-18B, the light sources Z201,  
16 Z203; Z202, Z204 would be generally in the horizontal plane of the central  
reflected light ray Z330 and at opposite sides of the reflected image receiving  
18 aperture Z312A, FIG. 17, to provide a coplanar light source/image receiver  
arrangement.

In an embodiment according to FIGS. 16-18B if the solid state light  
20 sources Z201, Z203; Z202, Z204 FIG. 13A were positioned above the horizontal  
22 plane of the central reflected ray Z532, and were directed somewhat downwardly

as represented by ray Z533, FIG. 14, and if the angle of the sloping plane of rays Z533 was not adjustable as represented by double headed arrow Z580, this non-coplanar arrangement would limit the depth of effective illumination since it is intended that the laser beams have a relatively narrow effective thickness dimension in comparison to that provided by the LED arrays Z291 and Z491. Thus a useful modification of FIGS. 14, 15, 19, and 20 for increased illumination depth would be to place solid state laser light sources Z201, Z203; Z202, Z204, (FIG. 13A), coplanar with the horizontal plane of central reflected ray Z532, (FIG. 14). This is readily accomplished as can be seen from FIG. 15.

## 7. Description of FIGS. 23-26

FIG. 23 illustrates a range and angle measurement system based on U.S. Patent 4,373,804, the first figure. In the present embodiment, laser light source means Z800 may comprise laser diode means Z801, FIG. 26, spreading optic means Z802 and selector means Z803, Z804 for selectively providing a vertically oriented fan beam or a horizontally oriented fan beam. Further beam divider means Z805-Z810, FIG. 26, of source means Z800 may serve to generate three vertically oriented fan beams such as indicated at Z811, Z812, Z813 or a single horizontally disposed fan beam such as indicated at Z831, FIG. 24, at bar code label Z832.

Where the three vertically oriented fan beams Z811, Z812, Z813 are directed toward a horizontally disposed bar code Z833, FIG. 24, they may impinge on the bar code as vertical lines with axes Z811A, Z812A, Z813A



distributed over a substantial portion of the bar code length so as to adequately  
sample any skew of the label Z832 relative to a normal axis Z834, FIG. 23.  
Range measurements at Z811A, Z812A, Z813A, for example, will differ as  
indicated by the displacements of point Z811A and Z813A from normal axis  
Z834 in FIG. 23. Where beams Z811, Z812, Z813 diverge so as to intersect bar  
code Z833 at respective generally equal segments, and the range  
measurements to points Z811A, Z812A, Z813A, FIG. 23, differ substantially,  
linear actuator Z650, FIG. 20, could be set in succession to the three measured  
ranges for reading the respective bar code segments Z833-1, Z833-2, and Z833-  
3, whereupon these three segments could be combined to obtain a complete bar  
code reading. Processing procedures for joining partial bar code readings are  
known in the art.

If it is desired to use crossed fan beams generated by a common laser  
diode source Z801, FIG. 25, then an analyzer plate Z804, FIG. 26, may be  
provided for transmitting only a horizontally polarized fan beam Z831, but  
blocking a vertically polarized fan beam. An LCD cell Z803 when energized may  
rotate the polarization of the input crossed fan beam such that beam Z831 is  
blocked and cross hair type fan beams Z811, Z812, Z813 are produced.

In this case, LCD cell Z803 is energized to provide the range and slope  
measurement mode of FIG. 23, and thereafter the LCD cell Z803 is de-energized  
to permit a bar code reading.

With the LCD cell 803 de-energized, the vertically disposed fan beam is intercepted at Z804, and the horizontally disposed fan beam with horizontally polarized light is transmitted by analyzer plate Z804 to the prism or mirror type beam splitter Z805-Z810 which spreads an incident fan beam disposed in the horizontal plane of FIG. 24 to cover a bar code such as indicated at Z833, FIG. 24. The constituent beams making up the overall beam Z831 are indicated by marginal rays Z831A, Z831B, Z831C, Z831D, Z831E, Z831F in FIG. 25.

Two laser diodes at Z801 with junction planes at right angles can supply the respective fan beams, using spreading optics such as Z203, Z204 for component Z802, FIG. 26.

The photodetector arrays such as Z851, Z852, FIG. 23, could be of the two dimensional matrix type, for example, so as to both sense the variable positions of the incident cross hair beams at Z811B, Z812B, Z813B, Z811C, Z812C, Z813C and to sense the spacial modulation of the reflected light beam Z831 due to bar code Z833. However, a linear CCD would most likely sense the bright spots at the code in most cases.

#### DESCRIPTION OF FIGS. 27-33

FIG. 27 is a perspective view illustrating a preferred terminal configuration 1010 of a size to be held in the hand of the user. FIG. 27 illustrates the placing of an information card 1011 into a receptacle 1012 of the terminal. The card 1011 may be a standard intelligent information card conforming with international standards such as the present ISO standard. Such a card may



have the same length and width and thickness as a standard credit card now in use. By way of example, such a card may have an array of eight contact terminals at one side thereof providing for interface with other devices. Such a card may have an electrically erasable programmable read only memory of a sufficient capacity to record an individual's account number, personal identification number and other information which may be desired for reliably identifying the individual. Further, such a memory may have a capacity for receiving extensive additional information such as might be required in effecting betting on a number of horse races.

By way of example, receptacle 1012 may be provided with nub means 1014 which is configured to cause the card 1011 to flex at its edge 1011a as it is pivoted into receptacle 1012. Thus the nub means 1014 may be spaced above the floor of the receptacle 1012 by a distance slightly greater than the thickness of the card. An opposite side edge 1011b of card 1011 may be inserted under similar nub means at the opposite side of receptacle 1012 and the card 1011 then pivoted downwardly until edge 1011a of the card is snapped under nub means 1014. The nub means at opposite sides of receptacle 1012 which cooperate with card edges 1011a and 1011b hold the card 1011 in receptacle 1012, and spring urged contacts in the floor of receptacle 1012 make pressure engagement with the array of eight contacts on the underside of the card, once the card has been inserted.



Any suitable means may be employed to facilitate removal of a card from the receptacle 1012. For example, a wall 1015 of terminal 1010 may be provided with a notch 1016 enabling insertion of a fingernail or stylus under edge 1011a of the card for prying the card upwardly and out of the recess. The standard card 1011 is sufficiently flexible so that this is readily accomplished.

In the embodiment of FIG. 27, a touch screen 1017 occupies the side of the terminal opposite receptacle 1012 and has an area generally comparable to the area of the standard card. By way of example, the touch screen may utilize LCD (liquid crystal display) technology and may be capable of displaying a number of lines of characters, for example four lines relating to four bets and additional lines which may, for example, provide an integrated graphic display (e.g., a single line of Chinese characters).

By way of example, associated with the touch screen at a surface 1020 may be suitable indicia such as 1021-1024 for explaining the format of the display. In the specific illustration of FIG. 28, the characters "HV" may represent the initial letters of the name of a race track (e.g., Happy Valley), the next series of characters representing the data (e.g., year, month and day of month). Further characters on the display may relate to the day of the week, the type of bet or the like.

In the example of a transaction involving betting on a horse race, an exemplary keyboard display for touch screen 1017 is indicated in FIG. 29. In an example where several race tracks may be involved, the identities of respective





race tracks may be displayed at locations such as 1031 and 1032 in FIG. 29.

Each location may display indicia indicating the programmed significance of the location. Simply by way of example, a prompt message at lines 1033 and 1034 might instruct the user to select the race track where the race to be the subject of a wager is to take place. At the same time indicia representing the two race tracks would appear at 1031 and 1032. The user would then press location 1031 or 1032 with his finger to indicate the identity of the race track. A similar procedure could be followed for identifying the day of the race, the number of the particular horse on which the bet is being placed, the amount of the wager, and so on.

In the preferred embodiment of FIGS. 27 and 28, the terminal 1010 is provided with an acoustic coupling means 1050 which may serve to couple the terminal with telephone lines, for example. Thus in the case of betting transactions, once the user of the terminal has entered desired bets, for example on a number of horse races, the user may couple the terminal, e.g. via an acoustic coupler, with a handset of a conventional telephone, for establishing two-way telephone communication with a central computer system equipped to deal with the particular type of transaction and to authorize the individual participant. The touch screen 1017 may display suitable prompt messages in establishing the telephone link with the central computer, or the processor of the terminal 10 may itself be programmed to establish the telephone link automatically, for example in response to actuation of a "SEND" location 1035 of



FIG. 29. Once communication is established, the processor of terminal 1010 is able to transmit the data stored on the information card 1011 via the telephone link to the central computer system so that the central computer system can verify that the individual is authorized to carry out the relevant transactions. In the case of horse race betting, the information on the particular race and particular horses involved and the other details of the bet would be transmitted to the central computer system for verification and for evaluation of the total amount being bet, for example in relation to the individual's established account balance.

Also in the preferred embodiment as shown in FIG. 28, the housing is provided at a corner thereof with an optical scanner module 1060 which may be utilized as a hand-held bar code scanner, and which also can serve for receiving optical communication via a suitable receiving device. In the case where the terminal utilizes rechargeable batteries, a receiving boot could automatically couple with a charging circuit for the battery means and this boot could also be provided with a host computer or suitable communication to a host computer system such that data from the intelligent card 1011 and from the memory of the terminal itself could be communicated with the host system via an optical link including the scanner module 1060, if desired.

Also as a preferred implementation, FIG. 30 illustrates a suitable processing system for the housing 1010, including a microcontroller 1070, a real-time clock 1071, control and communication circuits 1072, EPROM 1073,

random access memory components 1074 and 1075, a wand scanner and optical interface component 1077, an acoustical coupler interface 1078 and a module 1080 for controlling character and/or graphic display of the touch keyboard screen for a particular desired application.

By way of example, intelligent information card 1011 may be approximately 3-3/8 inches by 2-1/8 inches (about 9.5 centimeters by 5.4 centimeters). The dimensions of displays 1017, FIG. 28 and 1117, FIG. 31 are thus approximately comparable to the length and width of the card. (The card thickness is standard and about 1/32 inch). In FIGS. 27-30, the overall dimensions of the terminal 1010 are not substantially greater than the corresponding card dimensions; the thickness is such that terminal 1010 fits in an ordinary shirt pocket. By way of example, the terminal may have a thickness of less than one inch, i.e. less than 2.5 centimeters.

In the development of a preferred pocket-size terminal such as indicated in FIGS. 27 and 28, it is sometimes convenient to utilize a larger development terminal such as indicated at 1100 in FIGS. 31 and 32, which may utilize the same size of touch screen 1117, (i.e. two inches by three inches), but may further utilize a highly versatile keyboard 1120, and a much larger memory capacity so that many different features can be tried out for a particular application. At the rear of the touch screen 1117, there may be a receptacle 1125, FIG. 32, for an intelligent information card exactly corresponding to receptacle 1011 of FIG. 27. The terminal 1100 is shown as being provided with

an optical scanner module 1130 which may function in the same manner as the module 1060 of the preferred embodiment of FIGS. 27 and 28. In the example of FIGS. 31 and 32, rechargeable batteries may be utilized, and a boot receiving the housing of terminal 1100 may have provision for optical coupling with the computer system of the housing via an optical output means 1135. Optical communication from a host computer system may be via the optical scanner module 130 as in the embodiment of FIGS. 27-30. The housing of terminal 1100 is provided with an acoustical coupling means for telephonic communication corresponding to the acoustical coupling means 1050 of FIG. 27. An exemplary embodiment according to FIGS. 31 and 32 may utilize internal components as indicated in FIG. 33.

In the specific embodiment of FIG. 33, components 1140-1156 may have the functions and parameters as indicated by labels for the respective components in FIG. 33.

#### DESCRIPTION OF FIGS. 34 THROUGH 40

FIGS. 34, 35 and 36 show a shirt pocket size terminal configuration 1200 generally corresponding to that of FIGS. 27-30, but omitting the card receptacle 1012, terminal 1200 includes the following components:

- 1201 - casing
- 1202 - membrane keyboard
- 1204 - liquid crystal display
- 1206 - display drivers
- 1208 - batteries
- 1210 - real time clock
- 1212 - scanner module

1214 - scanner tip  
1216 - plastic support for membrane  
keyboard 202 (FIG. 8)  
1218 - printed circuit board  
1220 - display/keyboard controller  
1222 - RAM  
1224 - microprocessor  
1226 - ROM - A/D  
1228 - real time clock, decode circuits

Referring to the graphics display of FIG. 36, data input into unit 1200 may be by means of a touch screen display as indicated at region 1230, or by means of a digitizer system for sensing the position of a manually held stylus.

Exemplary characteristics for such a unit are summarized as follows:

**V25 CMOS MICROPROCESSOR 8 MHZ**

16 bit arithmetic logic unit  
8086 software compatible  
16K byte mask ROM  
retains VRTX operating system  
diagnostic/power control routines  
sophisticated loader

**1 MEGABYTE ADDRESS RANGE**

2 UARTS -  
Full Duplex  
Internal Baud Rate Generators

**RAM CMOS STATIC**

1 Megabyte- Less 16K ROM and 512 Internal RAM and SFR  
Holds Application Programs  
Also is Data Storage  
Battery Back-Up (Non-Volatile)

**REAL TIME CLOCK/CALENDAR**

Provides Date/Time Information  
Back-Up

**PLASTIC LCD DISPLAY**

64 X 128 Pixel Graphics Dot Matrix  
Built-In ASCII Character Generator  
Programmable Character Capability  
Limited Animation Capability

2    **TRANSPARENT KEYPAD**

4                    50 Keys in 5 x 10 Matrix  
                     Defined By Display For Location, Size, & Legend

6    **BUILT-IN WAND TYPE SCANNER**

8                    User Input Capability In Addition To Keypad

10   **RECHARGEABLE BATTERIES**

12                   Nicad or Lithium  
14                   Complete Control/Monitor Via Software  
                     Offers Highly Reliable Remaining Battery Operating Time  
16                   Gauge  
                     Provides power to RAM + RTC Under All Conditions

18   **I/O CONNECTOR**

20                   8 Pin  
22                   Programmable  
                     Only Ground and Charge Pins Dedicated  
24                   5 Volt Interface  
                     Never Powers Peripherals

26   **ENVIRONMENTALLY SEALED**

28                   Plastic Case is Glued or Sonic Welded  
30                   Repair Procedure Is To Cut Case Away and Replace  
32                   Can Be Submerged

DISCUSSION OF FIGS. 34, 35 AND 36

34

                     The main attractions of a V25 micro-controller for the system of FIGS. 34,  
36    35 and 36 are that it is CMOS, very high speed, and sixteen bits internal, with a  
                     nice collection of built-in peripherals. The fact it is 8086 software compatible  
38    means that VRTX (versatile real-time operating system) can easily be ported to

the V25, with the addition of new I/O drivers. VRTX is a multi-tasking operating system, so the battery control circuitry software will run at a fixed priority level at all times as will diagnostic routines. Applications will be moved in and out as necessary.

The one megabyte of CMOS static RAM and the RTC are always supplied power. When battery voltage drops below a selected value, e.g., 4.5 volts, (the fuel gauge will read zero at this point) the unit shuts down and cannot be worked unless proper power is supplied to it on its charge pin. The unit will appear to shut down when not actively doing anything; however, touching the keypad will bring it to use. (Also I/O activity will wake it.)

The plastic LCD display is light in weight and relatively immune to mechanical injury. The graphics capability is advantageous so that the display can define the keypad, key location, size, and legend. It will display icons and provide vertical and horizontal movement. The display controller can work from a page larger than can be displayed and move around in the page without rewriting the display memory. The ability to load-in custom character sets lets the unit perform I/O suitable to the country in which it is used (just by downloading new software).

The I/O may be strictly serial in operation; however, besides the two UARTS of the V25 there will be an 8530 SCC (serial communication chip) which will provide two more serial channels. This enables protocols to be run

synchronously as well as asynchronously. The 8530 will provide bit, byte, and  
2 A-Sync communication at a high data rate- up to 1.5 megabytes per second.

Pursuant to an early concept of peripheral shells, the unit can stand alone  
4 in a package tracking, meter reading, tree counting or warehouse/store inventory  
environment, but possesses a great amount of power and with more peripherals  
6 could well become the next generation of low and mid-range terminals. A shell  
would be used to envelope the unit and house the external peripherals and  
8 additional power source they would require. A hand-held computer unit could be  
composed of a keyboard and a fifteen pin I/O interface with the whole under  
10 keyboard area filled with alkaline batteries to power the peripherals and the V25  
core unit.

12 Similarly, a larger display, a printer, a permissive modem, an RF link  
module and other peripherals could be shelled around the core unit of FIGS. 34,  
14 35 and 36.

16 By way of example, the terminal unit of FIGS. 34, 35 and 36 may have a  
width of the order of two inches (e.g. 2 1/8 inches), a length of the order of three  
inches (e.g. 3 3/8 inches) and a thickness of the order of one inch (e.g. 3/4 inch).

18 In a digitizing input mode of operation of the unit of FIGS. 34, 35 and 36,  
successive character entry fields may be defined in a line across a screen area  
20 such as indicated at 1240. For example, the rectangle 1240-1 (presently  
containing the numeral "1") could receive a first character, e.g. manually entered  
22 as a series of strokes by means of a stylus. The unit could produce a graphical





display in the form of lines corresponding to the paths of the successive strokes,  
2 e.g. at the line 1242 above line 1240. The program could analyze the input on  
the basis of the sequence in which the strokes were entered, rates of stylus  
4 movement, and so on, so as to interpret the intended character with substantial  
accuracy. The unit may display its interpretation of a manual character entry by  
6 displaying the corresponding stored character from its repertory at a line 1244,  
e.g., as soon as there is a pause of selected (programmable) duration. If then  
8 the user begins drawing a new character, e.g., in a second field 1240-2, the  
program will assume that its interpretation is correct and will automatically store  
10 it. If a given field is skipped, a space may be correspondingly automatically  
stored. The size of each character field and other parameters (such as pause  
12 duration) can be selected to have values convenient to the individual user,  
during a user set up mode, with suitable prompts from the display. The  
14 processor, during manual character entry, can be set to a learning mode where it  
seeks to adapt as accurately as possible to the writing style of a given user.  
16 Such learning mode can be switched off whenever desired, as a further user set  
up mode parameter. A similar procedure could be followed for processor  
18 learning in the case of a speech input module.

FIG. 37 illustrates a shell module 1260 having a receptacle 1261 for  
20 receiving a processor core module such as 1200, FIGS. 34, 35 and 36. Module  
1260 may cooperate with module 1200 to provide a direct store delivery  
22 terminal. The terminal may have a card slot 1262 for receiving a conventional

smart card containing the information related to a delivery transaction, and may  
2 have an input/output coupler such as a one-fourth inch phone jack 1264 for  
coupling with a store device 1270, FIG. 38, via a connecting link such as 1272,  
4 FIG. 39. Phone jack 1264, FIG. 37, and phone jack 274, FIG. 38, may be one-  
fourth inch three-conductor phone jacks for receiving cooperating phone plugs  
6 1276, 1277 of link 1272.

The coupling between a smart card and a receiving terminal (such as  
8 1260, FIG. 37) is illustrated in the third figure at page 45 of an article entitled,  
"Smart Credit Cards: The Answer to Cashless Shopping" in IEEE Spectrum,  
10 February 1984 (pages 43-49) and this article is incorporated herein by reference  
by way of background. A similar coupling arrangement is preferred between  
12 modules 1200 and 1260.

By way of example the core module 1200 may have an array of eight I/O  
14 contacts similar to those of the smart card of the third figure at page 45 of the  
IEEE Spectrum article just referred to. These contacts would mate with  
16 cooperating contacts at a contact region such as indicated at 1280 of module  
1260. Charge and ground contacts of module 1200 could be of fixed function,  
18 while the other contacts could be programmable as serial channels, clocked  
data, analog inputs or outputs, or event inputs and outputs.

20 Module 1260 may have a battery compartment 1282 for receiving alkaline  
batteries for energizing suitable interface circuitry such as represented in the  
22 above-referenced third figure. A telephone jack may be located at 1284 for



coupling with the modem of the referenced third figure. Module 1200 may  
couple with the interface circuitry of module 1260 via contact region 1280 in the  
same way as represented in the referenced third figure for the case of  
"Peripherals" and/or as represented for the case of a "Display", and "Keyboard",  
for example. A customer keypad may be coupled with module 1260 in the same  
way as represented in the referenced third figure.

Typical shells for forming hand-held terminals with module 1200 could be  
printers, laser bar code readers, RF modules, smart card interfaces (as at 1262,  
FIG. 37), disk systems, full travel keyboards, larger displays, local area network  
interfaces, etc. A hand-held printer device which could serve as a shell for the  
processor module 1200 is available commercially from Norand Corporation,  
Cedar Rapids, Iowa, and is referred to as a 40-column hand-held printer for use  
in product distribution systems, and is described in a brochure designated "960-  
182-0485" of Norand Data Systems.

#### DISCUSSION APPLICABLE TO ALL EMBODIMENTS

The concept of a plural module hand-held data processing system  
enables the use of a single computing engine to drive an entire product line.  
The basic or core module may comprise a self-contained limited input/output  
device with extreme reliability and flexibility. While the core module can serve  
many markets directly, many more can be met by using peripheral device shell  
modules which may integrate the core module into its confines. An internal fixed

operating system protects the critical core module functions while allowing user applications to execute in a multi-tasking real time environment.

Of prime importance are the two requirements of low cost and tremendous capability. The lowest possible cost is achieved by use of technology yielding low manufacturing costs at high volumes. High volumes are achieved when a single product is flexible enough to perform well in multiple markets.

Of particular interest are flexible shirt pocket size plural module configurations which enable data input independently of a conventional keyboard. For example, a digitizer tablet input such as described with reference to FIGS. 34-39 is also applicable to the embodiments of FIGS. 27-33. Various optical type scanners are also of substantial utility for quick, easy and highly accurate input of existing printed data, e.g., bar codes, text, and graphical information. Instant type optical readers which may be integrated into a hand-held shell module according to the present invention are disclosed in an application of Danielson and Durbin, Serial No. 07/894,689 filed August 8, 1986, now U.S. Patent No. 4,877,949, issued October 31, 1989, and the disclosure including the drawings of this incorporated Danielson and Durbin application (07/894,689) are incorporated herein by reference in their entirety as illustrating arrangements which may be embodied in a peripheral shell such as indicated at 1260A in FIG. 40, which is analogous to shell 1260 in FIG. 37. For the embodiments of this incorporated Danielson and Durbin application (07/894,689), the optical output means in FIG. 40 may be at opposite ends of

battery compartment 1282A (corresponding to compartment 1282, FIG. 37) at  
2 locations such as indicated at 1313A in FIG. 40, while the reflected light optics  
and processing components may occupy the region below compartment 1282A  
4 FIG. 40, and a region replacing card slot 1262, FIG. 37, such location being  
designated by reference numeral 1314A in FIG. 40. The control and processing  
6 means of said Danielson and Durbin incorporated application could be  
embodied in the basic core module such as represented at 1200 in FIG. 34, or,  
8 as represented in FIG. 40, the display and manual data input means could be  
provided by a separate module 1200A in receptacle 1261A in FIG. 40, while a  
10 basic processing module occupied a greatly reduced space such as represented  
at 1300A in FIG. 40, the processing module being inserted into a receiving well  
12 via a removable cover as is commonly the case with battery compartments such  
as 1282 in FIG. 37. Such a cover, could incorporate resilient means so that  
14 when the cover was latched, a core processing module at location 1300, FIG. 37  
would have its eight metal contacts pressed against cooperating contacts of the  
16 receiving shell module such as 1260. Referring to the article "Smart Cards" by  
Robert McIvor in Scientific American, November, 1985, at page 153, an eight  
18 contact terminal is shown in association with a single chip microprocessor  
system, from which it will be apparent that the width of the smart card could be  
20 reduced from fifty-four millimeters to twenty millimeters and fit edgewise into the  
region 1300 (vertically as viewed in FIG. 37). For such a strip type core module,

the thickness could be substantially greater than the standard card thickness of .76 millimeters, for example ten millimeters.

The core module may incorporate the components of FIG. 30 or FIG. 33, or components such as 1077, 1078 and 1080, FIG. 30, may be incorporated into a peripheral device module, for example one fitting into receptacle 1261 of shell module 1260, the core module incorporating the remaining components. Similarly as to FIG. 33, components such as 1147, 1148, 1149, 1150 and 1151 can be incorporated into a module fitting into receptacle 1261, while component such as 1152 and 1154 may be incorporated into the shell module 1260, and the remaining components incorporated into the strip core module fitting into region 1300.

Preferred features of an exemplary core module such as might fit into receptacle 1012, FIG. 27, receptacle 1125, FIG. 32 or region 1300, FIG. 37, are as follows:

(1) User immune real-time multi-tasking operating system. The multi-tasking ability allows system programs of the core module to run in the background and never lose control. This ensures proper operation of the user's application(s) and system status availability.

A program known as VRTX (Versatile Real-Time Executive) and IOX (Input/Output Executive), available commercially, together with input/output drivers, monitors and control programs preferably compose the operating system stored in the core module (for example in read only memory ROM).



(2) A microcomputer compatible with personal computer architecture,

e.g., an NEC V25 microcomputer with 8086 type architecture, supports the implementation of the operating system in that VRTX and IOX are 8086 oriented.

A high integration CMOS construction directly supports the lower power standby and shut down features which are desired for the core module versatile interface adapter (VIA) software control. A one megabyte addressing range would be considered a minimum for hand-held units, along with a sixteen bit internal arithmetic logic unit.

(3) With a one megabyte memory, for example, read only memory necessary to contain the operating system would require about eighty kilobytes. All the rest of memory in the addressing range may be CMOS static random access memory used for applications.

(4) The core module preferably provides clock and calendar functions, and a hardware real time clock chip is compatible with very low power requirements.

(5) Battery operation is presently a key hardware aspect of a core module, and this is the main reason VRTX should provide immunity from the user. In order to offer unparalleled reliability in the field, the power control system should never be tampered with except under operating system control. The core module may use nickel cadmium rechargeable batteries. Such a core module preferably implements the intelligent battery system such as disclosed in U.S. Patents 4,455,523, 4,553,081 and in a pending application of Steven E.

Koenck, et al., U.S. Serial Number 876,194, filed June 19, 1986, now U.S. Patent Number 4,709,202. The intelligent battery system allows a very accurate "fuel gauge" for advising the user of remaining battery capacity. Fast charge capability offsets the lower capacity batteries which are preferably used in the core module. All of the RAM, the RTC and internal registers, e.g., of the V25 are battery backed up, even with the unit shut down.

Battery monitoring will also indicate possible problems before they become serious and, combined with other system monitoring, will provide unprecedented forewarning of possible impending failure. All devices will ultimately fail, but it is extremely advantageous if a unit can be removed from service before a hard failure occurs.

(6) The core module should be able to communicate with a host and with peripheral devices, for downloading of the application programs into the core module and for communicating with all types of input/output devices such as those referred to herein. Extensive flexibility in the communication protocol is provided for example by using two high speed serial channels capable of being programmed as asynchronous, byte synchronous or bit synchronous. Eight input/output contacts provide electrical connection to the outside. The charge and ground contacts may be fixed while the other contacts may be programmable as serial channels, clocked data channels, analog inputs or outputs, or event inputs and outputs. The concept of using peripheral shell modules for selective coupling with the core module offers complete expansion



capability with minimal development time to enter new markets. Typical shell modules could comprise graphics LCD display means providing a touch keyboard, digitizer tablet means, printers, laser bar code readers, RF modules, smart card interfaces, disk systems, full travel keyboards, larger displays, local area network interfaces, et cetera. Optionally, as illustrated in FIGS. 34, 35 and 36, for example, the core module may have a built-in minimal input/output capability such as may be achieved by using a graphics LCD display on one face of the core module for output and a touch responsive keyboard directly behind and defined by the display. The display, for example, may comprise 64 x 128 pixels, or eight lines by twenty-one characters, and may support any character set that can be defined. This is ideal for foreign applications. Since the keyboard is defined by the display, it will naturally be in the same language. The display (and keyboard) may be backlit by a built-in electroluminescent panel. Many stand-alone applications for such a core module would require bar code scanning and thus a built-in scanner is illustrated at 1212, 1214, FIG. 34. Such a display would have the ability to use icons (pictorial images) as labels for keyboard locations, and to change them as the application requires.

A core module such as shown in FIGS. 34 and 35 could have a housing comprised of two die cast magnesium shells, glued together. Preferably there are no holes through the housing, so that the unit is submergible. It is ideal for meter reading, package tracking, timber inventory, or any environmentally demanding application. Internal construction is preferably of one continuous

flexible printed circuit board. This eliminates connectors, weight, and sources of failure. Preferably even the batteries are soldered in. The core module may withstand being dropped to a concrete surface from seven feet without functional damage. A minimum number of integrated circuits will reduce the cost and increase the reliability of the core module.

Where the graphics type keyboard displays icons representing physical objects, it will be apparent that such physical objects may be represented by a single code word such as utilized to represent any other keyboard entry. Such code may be translated into a corresponding graphical icon type display by means of a suitable read only memory or the like. A similar situation can prevail for example where shorthand characters are input to respective receiving regions such as indicated at 1240-1 and 1240-2 in FIG. 36. Spoken words related to a given application may likewise be represented by single code words in random access memory, and translated via read only memory or the like into corresponding strings of characters for display, or for synthesized speech output. As previously mentioned, if the letter P is related to a number of objects for a given user application, the user may input the letter "P" at a region such as 1240-1 or 1240-2, FIG. 36, whereupon the input strokes may be repeated at a corresponding location in row 1242, and possible interpretations, either graphically, or as character strings, may be sequentially presented, e.g. at row 1244. When the correct interpretation is displayed, the user may touch a

suitable region of the display such as indicated at 1310 to indicate approval of  
2 the current displayed interpretation.

In preferred hardware for implementing the illustrated embodiments, all  
4 memory and input/output accesses are allowed when the system is in the  
supervisor or system mode. On the other hand, any access by an application  
6 program to any area outside of its work and program areas (as assigned by the  
system) must immediately return control to the operating system for proper  
8 action. A microcomputer such as the V25 is advantageous because of its non-  
multiplexed bus, and built-in software-controlled power down. It would also be  
10 advantageous to have a built in hardware boundary checking of applications  
being run (as in the 80286). A digital semi-custom chip can accommodate this  
12 function externally.

A V25 internal timer may be used as the VRTX tick. Entrance to VRTX is  
14 through the NMI input of the V25. This is the only input (besides reset) that not  
only can wake the chip up if it's in a sleep mode, but also cannot be shut off by  
16 an application (thus disabling VRTX). Many sources may logically OR into NMI.  
The real-time clock, serial channels, charge indicator, and keyboard are some of  
18 these. Most of these should be programmable as to whether they can activate  
NMI.

20 The random access memory can be built as a separate module. For  
example eight 128 kilobyte chips and decoding may be in the module. A module  
22 select line should also be included since the module is expected to be useful in



other product lines in multiple configurations. Standby currents of fifteen microamperes at two volts are being presently considered.

As real-time clock, an Intersil 7170 may be used since it is guaranteed to operate at two volts, the same as for RAM. The RTC and RAM are all battery backed up once low battery condition is entered.

For a shell module containing a display, a plastic LCD dot matrix display from Polaroid Corporation may be used. A display size of 64 x 128 pixels with eighteen mil pitch gives eight lines of twenty-one characters each (5X7 font). The controller may be the Epson E-1330. This is a graphics controller that can support three separate planes or pages for the screen and can combine them in many different ways. The planes can be graphic or characters. The characters can come from the internal ROM or RAM loaded by the application. A graphics plane could create boxes and a character plane could put legends in them. The E-1330 uses S-MOS 1180 and 1190 drivers to run the columns and rows (respectively) of the display. They apply a ten to fifteen volt bias on the display. This may be obtained from a plus five volt supply in the core module in combination with a variable minus twelve volt supply in the shell module and providing two to three milliamperes for the display. This supply is controlled by the E-1330 as for on-off but the V25 will be responsible for controlling the actually used voltage based on the temperature of the core module and user input information. A fast recovery crystal is preferred to minimize the time delay upon release of pressure (e.g. by the manual entry stylus or finger). Using a fast

recovery plastic LCD display enables the user to press through the display and  
2 activate a keyboard behind it. The display is used to define the keyboard or  
provide the "overlay". This gives the advantage of not only being able to  
4 continually change the keyboard as the application requires, but if the display is  
programmed in a foreign language such as Ethiopian, the keyboard is in the  
6 same language. Putting the keyboard behind the display allows for an opaque  
design of low contact resistance. The keyboard may be a 5 x 10 matrix (fifty  
8 keys) software configurable to be combined for any shape or icon style key  
defined by the display.

10 A soft (but tough) electroluminescent panel is preferred for backlighting,  
the keyboard being activated by pressing through the display and the  
12 electroluminescent panel. A tremendous advantage here is that not only is the  
display operable at night, but so is the keyboard (which is further  
14 programmable!)

16 A built-in wand scanner such as indicated in FIG. 34 preferably has a  
sapphire lens in a stainless steel or other hard metallic housing. Testing has  
shown that sapphire tipped wands will chip concrete before they break. It is  
18 preferable to make the chip very rugged rather than to make it easily  
replaceable. The wand housing is preferably clamped (and glued) right into a  
20 casing such as 1201. The light source may be a near infrared visible LED to be  
able to read non-carbon inks and let the user know it is on, yet take advantage  
22 of the infrared capacity to read through many stains and smudges. Preferably



the scanner is capable of reading in direct sunlight, and in this connection  
reference may be made to an application of Eric J. Danstrom, U.S. Serial  
Number 07/044,820 filed April 30, 1987, the disclosure including the drawings of  
which being incorporated herein by reference in its entirety.

An initial approach of a four N-cell nickel cadmium battery pack with each  
cell treated individually is now less preferred than a one cell "battery pack". The  
one cell pack requires a converter to boost the voltage. The single cell has  
many more advantages. No cell matching is required. No conditioning cycles  
are required, and it is not necessary to be concerned about cell voltage  
depression. A single converter to step up the voltage for a shell display module  
would be suitable, with a single switching regulator (current mode) to charge the  
cell from a much wider input range (e.g. from four to twenty volts). Fast charging  
on the order of 1C (or perhaps 2C) can be achieved since continuous monitoring  
of cell voltage and temperature curves (with respect to previous cell conditions)  
will allow proper charging with no risk of overcharge. This same monitoring  
applied to discharge as well, provides a very accurate "fuel gauge".  
Rechargeable lithium batteries may be considered, but the general  
recommended operating requirements do not match the preferred embodiment  
as described herein as well as nickel cadmium batteries. The charging line will  
have a diode blocking reverse current flow and inserted prior to the input/output  
terminal (for protection). This same single battery pack may also serve as the  
backup battery. The operating system may operate to equate ten percent or



twenty percent of remaining capacity in the battery pack to "zero" on the "fuel gauge" being displayed to the user.

In a preferred embodiment a surface type connector as used in smart cards has advantages in that it takes up very little space and cannot clog with dirt (can be wiped clean, e.g., during interconnecting of respective modules). Further, a surface type connector avoids the use of a cable. To maintain input/output protection and immunity from the environment, each core module may have all of its programmable input/output terminals disabled. The charge pin of a core module may be used to determine the presence of a peripheral shell. Each peripheral may have its own power supply and may or may not provide charge to the core. A peripheral module must at least provide a logic ONE (greater than one volt) to the charge pin in order to signal its presence. If such a logic ONE is present, the core module will determine if the peripheral module can charge it by enabling the charge regulator on the charge pin. If the level pulls low, it will indicate that the peripheral module is meant to only communicate with the core module but not charge it.

Preferably immediately inside of the case of a module will be an electrostatic discharge (ESD) resistor/diode clamp protection scheme. From there the I/O lines may go to a crosspoint type multiplexing circuit. Since in a preferred embodiment any of the six remaining pins can be inputs or outputs and connect to A/D channels in the module, voltage measurements could be made in



a peripheral, e.g., by the core module and appropriate messages displayed to the user as to peripheral readiness and power levels.

The eight contacts of each module could be gold plated or the like such that they would be very conductive and yet tough. The contacts may be molded in a plastic insert that is glued into a hole at a location such as indicated at 1280, FIG. 37, for example.

A case such as indicated at 1201 in FIG. 34 can be in two pieces a front half and a back half, and the back half may have one rectangular flanged hole in which to glue the oppositely flanged I/O contact plate. The back half may be glued with conductive epoxy glue to the top case half. The top case half may have a large rectangular opening in which the display/electroluminescent panel/keyboard assembly fits. There may be a shelf behind this assembly for support with a glued-in bezel to seal the display and other components into the depression.

In an embodiment such as FIG. 34, preferably the mating corner portions of both halves may be specially molded to clamp around the scanner housing. When finally glued together, the resulting casing 1201 may be completely sealed. It may be water and gas tight, but preferably not hermetically sealed where the display plastic is permeable. Purging the casing such as 1201 with dry nitrogen at the time of assembly and sealing may increase reliability. Operation may be from somewhat below sea level (e.g. actually under water) up to 10,000 feet. The case such as 1201 may have a size a little over three inches



long by a little over two inches deep by about three-fourths inch thick, for  
2 example.

A module such as indicated in FIGS. 34, 35 and 36 would be suitable by  
4 itself for fields such as package tracking, price checking, inventory control, meter  
reading, consumer comparative shopping, et cetera. Various countries may  
6 require individually designed modules to couple with the module or module  
assembly of FIGS. 34, 35 and 36, in order to meet national requirements and the  
8 like, e.g., with respect to such peripheral devices as modems, power supplies  
and so on.

10 The core module previously referred to as being insertable into a space  
such as 1300, FIG. 37, may also be insertable into a similar space in the module  
12 of FIGS. 34, 35 and 36, and may represent a standardized basic processing  
module having the real-time multi-tasking operating system and other  
14 characteristics previously described herein.

16 It will be apparent that many modifications and variations may be effected  
without departing from the scope of the teachings of the present disclosure. For  
example, scanner tips such as indicated at 1060, FIG. 28, or at 1214, FIG. 34,  
18 may be adapted to left-handed users, by inverting the contents of the display.  
Thus, if tip 1214, FIG. 36, would be at the lower left with an upright display as  
20 shown in FIG. 36 for right-handed manual data entry, the module 1200 might be  
turned by a left-handed user so that the tip 1214 was at the upper right, and the  
22 contents of the display inverted.

DESCRIPTION OF FIG. 41

2 Reference is made pursuant to 35 U.S.C. Section 120 to Arvin D.  
Danielson and Dennis A. Durbin application for patent Serial No. 07/894,689  
4 filed August 8, 1986, now U.S. Patent No. 4,877,949, issued October 31, 1989,  
and the disclosure of the specification, including the claims, and the drawings of  
6 said application are hereby incorporated herein by reference.

A module such as shown at 1200B in FIG. 41 may have a non-contact  
8 essentially instantaneous bar code scanner, e.g., at a long edge such as 1311X  
in FIG. 41. Flash illumination where needed for the instantaneous bar code  
reader could be provided by a receiving shell 1260B such as shown in FIG. 41.  
10 The shell could contain the battery power for the flash illumination means in the  
shell and also for any LED marker light sources associated with the photodiode  
12 array of the processor module. A series of light emitting diodes at locations  
indicated at 1313B in FIG. 41 could be used for each of the flash illumination  
14 sources of the second and third figures of the incorporated patent application  
No. 07/894,689, and such LEDs could all be energized with simultaneous  
16 electric pulses, or the pulses could be supplied in quick succession to  
essentially simulate an instantaneous flash. Where the long edge 1311X in FIG.  
18 41 contains the scanner window for receiving a reflected bar code image, the  
receptacle 1261B in FIG. 41 could be shaped so that edge 1311X in FIG. 41  
20 faces frontally, and a frontal face (of a greater dimension than in FIG. 37) such  
as 1312B of the shell module 1260B in FIG. 41, would contain the flashable light  
22

source means, located as at 1313B in FIG. 41, for example. The processor  
2 module and shell, when assembled, would be hand held in operation, and could  
be of overall size to fit in a shirt pocket.

4 It will be apparent that many further modifications and variations may be  
effected without departing from the teachings and concepts of the present  
6 disclosure.

**CLAIMS**

What is claimed is:

1. In a data acquisition system, a hand-held data processing assembly, comprising:

(a) a base unit of size to be held in one hand during data acquisition;

and

(b) indicia reader module means, assembled with said base unit, containing a reflected light indicia reader for non-contact essentially instantaneous reading of bar codes or the like disposed in spaced non-contacting relationship to the assembly.

2. A data acquisition system according to claim 1, wherein said base unit comprises a light source for generating a light beam, the hand-held data processing assembly being orientable for directing a light beam from said light source toward the bar code or the like to be read.

3. A data acquisition system according to claim 1, wherein said indicia reader module means further comprises processing means for controlling the functioning of the hand-held data processing assembly.

4. A data acquisition system according to claim 1, wherein said base unit further comprises a battery for providing electrical power to the hand-held data processing assembly.

5. The data acquisition system according to claim 1, wherein said indicia  
2 reader module means further comprises a radio apparatus for wireless  
communication with components of the data acquisition system which are  
4 located remotely from the hand-held data processing assembly.

6. The data acquisition system according to claim 5, wherein said indicia  
6 reader module means further comprises an external antenna having a free end  
and wherein the reflected light indicia reader of said indicia reader module  
8 means further comprises a charge coupled device reader assembly capable of  
reading optical indicia located beyond the free end of the antenna.

10 7. The data acquisition system according to claim 5, wherein the reflected  
light indicia reader of said indicia reader module means further comprises a pair  
12 of laser diode sources and a single rotor for simultaneously directing light  
generated by said pair of laser diodes toward optical indicia to be read.

14 8. The data acquisition system according to claim 6, wherein the reflected  
light indicia reader of said indicia reader module means further comprises a pair  
16 of laser sources, each laser source coupled with optics apparatus, for essentially  
instantaneously illuminating optical indicia to be read by the charge coupled  
18 -device reader assembly.

**ABSTRACT OF THE DISCLOSURE**

2 A portable, hand-held data processing assembly of modular structure  
includes a base unit with a keyboard and a display screen. An indicia reader  
4 module is housed in a housing shell which is attachable to the base unit. The  
indicia reader module can contain a reflected light indicia reader for non-contact  
6 essentially instantaneous reading of bar codes of the like disposed in a spaced,  
non-contacting relationship to the assembly. The indicia reader module can also  
8 include a processor. The base can include a light source. Additionally, the base  
unit can include a battery for powering the hand-held data processing assembly.

10 A data collection and communications module can include a stacked  
arrangement of a communications interface main circuit board, a radio and a  
12 laser scanner assembly which are housed in a housing shell attachable to the  
base unit. In this arrangement, the radio is mounted in spaced relationship to  
14 one side of the main circuit board, while the laser scanner assembly is mounted  
to the other side of the main circuit board. A support frame and a plurality of  
16 ground planes in the sandwiched main circuit board and a routing circuit board  
form an RF cage for shielding RF interference which may be generated by the  
18 radio. Also disclosed is a method for reducing the operational power  
consumption requirements of laser bar code scanners by analyzing reflected  
20 laser light in order to determine the presence of optically readable information  
sets.




FIG. 1




FIG. 2




FIG. 3




FIG. 4






FIG. 5





FIG. 7

FIG. 6






FIG. 8





FIG. 9






FIG. 11

FIG. 12





FIG. 13A






FIG. 13B




FIG. 13C







FIG. 16







FIG. 17








FIG. 20




FIG. 21




FIG. 22




FIG. 23



FIG. 24




FIG. 26




FIG. 25




FIG. 27




FIG. 28




FIG. 29




FIG. 30








FIG. 33






FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 39




FIG. 38




FIG. 40




FIG. 41

**DECLARATION AND  
POWER OF ATTORNEY**

As a below named inventor, I hereby declare that my residence, post office address and citizenship are as stated below next to my name; that I verily believe that I am an original, first, and joint inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled:

“LASER SCANNER MODULE HAVING INTEGRAL INTERFACE  
WITH HAND-HELD DATA CAPTURE TERMINAL, PROXIMITY  
AND LABEL SENSING, AND ENHANCED SENSITIVITY AND  
POWER EFFICIENCY”

described and claimed in a specification assigned Application No. 08/438,220, and filed on May 9, 1995.

I hereby state that I have reviewed and understand the contents of the above-identified application, including the claims.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, Sec. 1.56(a).

CLAIM FOR BENEFIT OF EARLIER U.S.  
APPLICATIONS UNDER 35 U.S.C. 120

I hereby claim the benefit under Title 35, United States Code, Section 120, of any United States applications that are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in those prior applications in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56:

PRIOR U.S. APPLICATIONS FOR WHICH  
BENEFIT IS CLAIMED UNDER 35 U.S.C. 120

<u>U.S. Serial No.</u>	<u>U.S. Filing Date</u>	<u>Named Inventor</u>	<u>Status</u>
08/215,115	03/17/94	Koenck, et al.	Pending
07/987,574	12/08/92	Koenck, et al.	USP 5,313,053
07/674,756	03/25/91	Koenck, et al.	Abandoned
07/777,393	12/06/91	Koenck, et al.	Pending
07/364,902	06/08/89	Danielson, et al.	Abandoned
07/364,594	06/07/89	Cargin, et al.	Abandoned
07/965,983	10/23/92	White, et al.	Abandoned
07/719,731	06/24/91	White, et al.	Abandoned
07/441,007	11/21/89	White	Abandoned
06/905,779	09/10/86	White	USP 4,882,476
07/960,520	10/13/92	Hanson	Abandoned
07/912,917	07/13/92	Hanson	Abandoned
07/881,096	05/11/92	Hanson	Abandoned
07/820,070	01/10/92	Hanson	Abandoned
07/786,802	11/05/91	Hanson	Abandoned
07/777,691	10/10/91	Hanson	Abandoned
07/735,610	07/23/91	Hanson	Abandoned
07/674,756	03/25/91	Koenck, et al.	Abandoned
07/660,615	02/25/92	Koenck, et al.	USP 5,218,187



(Prior U.S. applications continued)

<u>U.S. Serial No.</u>	<u>U.S. Filing Date</u>	<u>Named Inventor</u>	<u>Status</u>
07/633,500	12/26/90	Danielson, et al.	USP 5,202,817
07/561,994	07/31/90	Cargin, et al.	Abandoned
07/558,895	07/25/90	Koenck, et al.	Abandoned
07/426,135	10/24/89	Hanson	USP 5,218,188
07/347,849	05/03/89	Miller, et al.	Abandoned
07/347,602	05/03/89	Miller, et al.	Abandoned
07/345,200	04/28/89	Hanson	Abandoned
07/305,302	01/31/89	Miller, et al.	Abandoned
08/040,313	03/29/93	Danielson, et al.	Pending
07/451,322	12/15/89	Danielson, et al.	USP 5,227,614
07/143,921	01/14/88	Danielson, et al.	Abandoned
06/897,547	08/15/86	Durbin, et al.	Abandoned
07/947,036	09/16/92	Durbin, et al.	USP 5,308,966
07/875,791	04/27/92	Danielson, et al.	Abandoned
07/422,052	10/16/89	Danielson, et al.	Abandoned
06/894,689	08/08/86	Danielson, et al.	USP 4,877,949

PRIOR PCT INTERNATIONAL APPLICATIONS  
DESIGNATING THE U.S. FOR  
BENEFIT UNDER 35 U.S.C. 120

<u>PCT Application No.</u>	<u>PCT Filing Date</u>	<u>Status</u>
PCT/US90/03282	June 7, 1990	USP 5,410,141

I hereby appoint as my attorneys, with full powers of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected herewith:

William M. Wesley	Reg. No. 26,521
George P. McAndrews	Reg. No. 22,760
John J. Held, Jr.	Reg. No. 21,061
Timothy J. Malloy	Reg. No. 25,600
L. Michael Jarvis	Reg. No. 27,341
Robert C. Ryan	Reg. No. 29,343
Gregory J. Vogler	Reg. No. 31,313
Herbert D. Hart, III	Reg. No. 30,063
Robert W. Fiesler	Reg. No. 31,826
Jean Dudek Kuelper	Reg. No. 30,171
Steven J. Hampton	Reg. No. 33,707
Alejandro Menchaca	Reg. No. 34,389
Priscilla F. Gallagher	Reg. No. 32,223
Robert B. Polit	Reg. No. 33,993
George F. Wheeler	Reg. No. 28,766
D. David Hill	Reg. No. 35,543
Christopher C. Winslade	Reg. No. 36,308
Thomas J. Wimbiscus	Reg. No. 36,059
John S. Artz	Reg. No. 36,341
Gregory C. Schodde	Reg. No. 36,668
Edward A. Mas	Reg. No. 37,179
Patrick J. Arnold	Reg. No. 37,769
all of McAndrews, Held & Malloy, Ltd., 34th Floor, 500 West Madison Street, Chicago, Illinois 60661	

Sean Patrick Suiter of Omaha, Nebraska	Reg. No. 34,260
---	-----------------

R. Lewis Gable of Washington, D.C.	Reg. No. 22,479
---------------------------------------	-----------------

H. Robert Henderson	Reg. No. 18,486
Michael O. Sturm	Reg. No. 26,078
Richard L. Fix	Reg. No. 28,297
Curtis A. Bell	Reg. No. 36,742
all of Des Moines, Iowa	

Robert J. Jondle	Reg. No. 33,915
Daniel B. Greenwood	Reg. No. 35,885
both of Omaha, Nebraska	

John E. Cepican of Davenport, Iowa	Reg. No. 26,851
---------------------------------------	-----------------

William H. Wright  
Martin J. Mullen  
both of Washington, D.C.

Reg. No. 26,424  
Reg. No. 28,574

Donald R. Schoonover  
John H. Sherman  
both of Cedar Rapids, Iowa

Reg. No. 34,924  
Reg. No. 16,909


Please direct all telephone calls to Jack Sherman at Telephone No.  
319/369-3661.

Address all correspondence to:

McAndrews, Held & Malloy, Ltd.  
34th Floor  
500 West Madison Street  
Chicago, IL 60661

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Signed on 5/15/, 1995

  
Arvin D. Danielson

Residence: Solon Johnson Iowa  
City County State

Post Office Address: 1560 Bramblewood  
Solon, IA 52333

Citizenship: United States of America

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Signed on May 17, 1995

Dennis A. Durbin  
Dennis A. Durbin

Residence: Cedar Rapids Linn Iowa  
City County State

Post Office Address: 140 Cambridge Drive N.E.  
Cedar Rapids, IA 52402

Citizenship: United States of America

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Signed on August 12, 1995

George E. Hanson  
George E. Hanson

Residence: Andover Butler Kansas  
City County State

Post Office Address: 225 Lioba Drive  
Andover, Kansas 67002

Citizenship: United States of America